

Section

HV Insulation

Application

Field



PRODUCT BENEFITS

Back-iron to set the pitch of the tool making easy to rotate the tool

TOOL CAPACITY

Diameter 60 - 80 mm
2,362 - 3,150 inch

Max cutting depth 24 mm / 0,945 in

TOOL DIMENSIONS

Length 460 mm

Width 130 mm

Height 85 mm

Weight without box 3 Kg

Packaging None

Monofunction tool for insulation

TO DO WHAT

The LH3 enables the user to remove the insulation



Spare part

LAC3 - Spare blade for insulation

Associated tool

LHS3 - Monofunction tool for semiconductor

PRG4/C30-L283335 - Pliers for MV cable outer sheath with 3 adjustable longitudinal cutting depth

BMF2 - Thrust to stop the tool

HV cables Tools

LH3



Part Number	D iameter	Tool capacity	D imensions			Packaging
		Max cutting depth	Length	Width	Height	
LH2	38 - 60 mm 1,496 - 2,362 in	17 mm / 0,669 in	425 mm 16,732 in	105 mm 4,134 in	85 mm 3,346 in	none
LH3	60 - 80 mm 2,362 - 3,150 in	24 mm / 0,945 in	460 mm 18,110 in	130 mm 5,118 in	85 mm 3,346 in	none
LH4	80 - 110 mm 3,150 - 4,331 in	29 mm / 1,142 in	640 mm 25,197 in	155 mm 6,102 in	95 mm 3,740 in	none
LH5	100 - 140 mm 3,937 - 5,512 in	35 mm / 1,378 in	730 mm 28,740 in	195 mm 7,677 in	115 mm 4,528 in	case



THORNE &
DERRICK
INTERNATIONAL

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com