

18.0 V CORDLESS HYDRAULIC CRIMPING TOOL



general features

B 35-45MDE

**18.0V
2.0Ah
Li-Ion**

Crimping force kN	Dimensions mm			Battery Li-Ion	Weight kg (with battery)
	length	height	width		
35	354	133	81	18.0V 2.0Ah	2,19

MAIN APPLICATIONS - max section mm²

L.V. lugs and splices	"C" sleeve Connectors	H.V. lugs and splices
150	35	70

STORAGE

Type	Dimensions mm	Weight kg	Supplied with the tool	Purchase separately
VAL P22	465x315x116	1,5	✳	—

The tool is supplied as:

- Basic tool with battery and wrist strap
- Spare battery
- Battery charger
- Plastic carrying case suitable for storing the tool and accessories



Can be operated with one hand. Balanced for greater control. Head rotates 180° for ease of operation in confined spaces. Fitted with a maximum pressure valve. Extremely quiet, minimal vibration. Durable moulded body offering high resistance to wear and damage in all operating conditions.

New Li-Ion 18.0V 2.0Ah High Power battery. The battery is equipped with LED indicators to show the remaining battery life at any time by pressing the adjacent button. Supplied in a robust plastic case to accommodate the tool and all the accessories. Two batteries and charger included.

New

**NEW
18V Li-Ion
BATTERY**



B35-45MDE accepts many of the dies common to 45 kN Cembre crimping tools. B35-45MDE specific dies available for crimping 120 mm² and 150 mm². Application field as shown in the table above. For further details please refer to tables of page 178-190. Operating temperature: -15 to +50 °C

Wide-opening head, ideal for derivations from running conductors



Motor ventilation



Head rotates 180° for ease of operation



Pressure release button



Sculptured body for optimum comfort

These tools are supplied without dies. For die selection, please refer to chart on pages 178 to 190