

B 35-50MDE

18.0 V CORDLESS HYDRAULIC CRIMPING TOOL

general features



Crimping force kN	Dimensions mm			Battery Li-Ion	Weight kg (with battery)
	length	height	width		
35	387	133	81	18.0 V 2.0 Ah	2,6

**18.0V
2.0Ah
Li-Ion**

New

**NEW
18V Li-Ion
BATTERY**



MAIN APPLICATIONS - max section mm ²			
L.V. lugs and splices	Insulated terminals	End sleeves	"C" sleeve Connectors
150	50	95	35

STORAGE				
Type	Dimensions mm	Weight kg	Supplied with the tool	Purchase separately
VAL P22	465x315x116	1,5	✱	—

The tool is supplied as:

- Basic tool with battery and wrist strap
- Spare battery
- Battery charger
- Plastic carrying case suitable for storing the tool and accessories



Can be operated with one hand.
Balanced for greater control.
Head rotates 180° for ease of operation in confined spaces.
Fitted with a maximum pressure valve.
Extremely quiet, minimal vibration.
Durable moulded body offering high resistance to wear and damage in all operating conditions.
New Li-Ion 18.0V 2.0Ah High Power battery.
The battery is equipped with LED indicators to show the remaining battery life at any time by pressing the adjacent button.

Supplied in a robust plastic case to accommodate the tool and all the accessories.
Two batteries and charger included.
B35-50MDE accepts many of the dies common to 50 kN Cembre crimping tools.

B35-50MDE specific dies available for crimping 120 mm² and 150 mm².
Application field as shown in the table above. For further details please refer to tables of page 178-190.
Operating temperature:
-15 à +50 °C



Wide-opening head, ideal for derivations from running conductors



Battery condition display



Pressure release button



Switch ergonomically designed



Automatic slot-in battery

These tools are supplied without dies. For die selection, please refer to chart on pages 178 to 190