### **MECHANICAL TOOLS HP4 RANGE**

### HP4-R



Professional manual mechanical tool with ratchet mechanism that prevents the handles from opening again before reaching the ratchet.

Equipped with a positioning device to reduce the operator's effort and facilitate proper crimping of the conductor. According to the different thicknesses of the conductor insulation, the crimping on the insulation can be carried out by adjusting the jaws through three different settings:

Te

### 1) strong, 2) medium, 3) light.

The tool is particularly easy to use thanks to its shape and handle coating.

At the end of the crimping the outer surface of the conductor is automatically stamped with the following crimping code:

one point for red conductor sizes from 0.25 to 1.5 mm<sup>2</sup>

### Construction features:

- Special treated and externally protected steel body, ratchet and handles.
- Handle coating in soft red PVC plastic.

Technical features:	HP4-R	Crimp style:
	Crimping range:	PVC, PC and PA6.6 insulated terminals and connectors for conductor sizes 0,25 to 1,5 sqmm
	Dimensions:	
HP4-R	Length (closed handles)	265 mm
	Width (closed handles)	80 mm
	Weight:	500 g
	Package dimensions:	330 x 110 x 50 mm





Professional manual mechanical tool with ratchet mechanism that prevents the handles from opening again before reaching the ratchet.

Equipped with a positioning device to reduce the operator's effort and facilitate proper crimping of the conductor. According to the different thicknesses of the conductor insulation, the crimping on the insulation can be carried out by adjusting the jaws through three different settings:

## 1) strong, 2) medium, 3) light. The tool is particularly easy to use

thanks to its shape and handle coating.

At the end of the crimping the outer surface of the conductor is automatically stamped with the following crimping code:

two points for blue conductor sizes from 1.5 to 2.5 mm<sup>2</sup>





### Construction features:

- Special treated and externally protected steel body, ratchet and handles.
- Handle coating in soft blue PVC plastic.

Technical features:	НР4-В	Crimp style:
13	Crimping range:	PVC, PC and PA6.6 insulated terminals and connectors for conductor sizes 1,5 to 2,5 sqmm
	Dimensions:	
	<b>Length</b> (closed handles)	265 mm
HP4-B	Width (closed handles)	80 mm
	Weight:	500 g
300	Package dimensions:	330 x 110 x 50 mm



### **MECHANICAL TOOLS HP4 RANGE**



#### Construction features:

- Special treated and externally protected steel body, ratchet and handles.
- Handle coating in soft yellow PVC plastic.



Technical features:	HP4-G	Crimp style:
15	Crimping range:	PVC, PC and PA6.6 insulated terminals and connectors for conductor sizes 4 to 6 sqmm
(HP1-BO)	Dimensions:	
	Length (closed handles)	320 mm
	Width (closed handles)	105 mm
	Weight:	810 g
100		



### HP4-G

Professional manual mechanical tool with ratchet mechanism that prevents the handles from opening again before reaching the ratchet.

Equipped with a positioning device to reduce the operator's effort and facilitate proper crimping of the conductor. According to the different thicknesses of the conductor insulation, the crimping on the insulation can be carried out by adjusting the jaws through three different settings:


#### 1) strong, 2) medium, 3) light.

The tool is particularly easy to use thanks to its shape and handle coating.

At the end of the crimping the outer surface of the conductor is automatically stamped with the following crimping code:

three points for yellow conductor from 4 to 6 sqmm





# HP4-C10

Professional manual mechanical tool with ratchet mechanism that prevents the handles from opening again before reaching the ratchet.

The tool is particularly easy to use thanks to its shape and handle co-

#### Construction features:

- Specially treated and externally protected steel body, ratchet and handles.
- Handle coating in soft yellow PVC.



Technical features:

HP4-C10	Crimp style:			
Crimping range:	For sleeve connectors type C6-C6 and C10-C10			
Dimensions:				
Length (closed handles)	325 mm			
Width (closed handles)	105 mm			
Weight:	730 g			
Package dimensions:	330 x 110 x 50 mm			

