

Demand Specification

General information

| | |
|----------|--|
| Customer | |
| Segment | |
| Project | |

Delivery time

| | |
|------------------|--|
| 1:st delivery | |
| Project duration | |
| Other* | |

Quantity

| | |
|----------------|--|
| Total quantity | |
| Other* | |

Quantity per batch

| | |
|-----------|--|
| One Batch | |
| Qty/batch | |
| Other* | |

Sealing demands

| | |
|-----------------------|--|
| No demands | |
| IP 54 | |
| IP 55 | |
| IP 65 | |
| IP 66/67 | |
| IP 68 (specify level) | |
| 0.1 Bar WP | |
| 0.5 Bar WP | |
| 1 Bar WP | |
| 2 Bar WP | |
| 4 Bar WP | |
| Constant pressure | |
| Gas pressure | |
| Blast load | |
| Exposed temp > 80C | |
| Retention demands | |
| Other* | |

Environment

| | |
|----------|--|
| Indoor | |
| Outdoor | |
| Offshore | |
| Ground | |
| Cabinet | |
| Shelter | |
| Other* | |

Frame Material

| | |
|------------------|--|
| Mild Steel | |
| Galvanized steel | |
| Stainless steel | |
| Aluminum | |
| Plastic | |
| Other* | |

Type of mounting

| | |
|---------|--|
| Bolting | |
| Casting | |
| Welding | |
| Other* | |

Surface treatment

| | |
|---------------------|--|
| Primed | |
| Natural anodized | |
| Chem. Nickel plated | |
| Powder coated | |
| Color code | |
| Untreated | |
| Other* | |

Wall structure material

| | |
|----------------|--|
| Steel | |
| Aluminum | |
| Concrete | |
| Gypsum | |
| Brick | |
| Sandwich | |
| Wall Thickness | |
| Other* | |

Fire

| | |
|--------------------|--|
| No Demands | |
| Civil Construction | |
| Marine | |
| Offshore | |
| One side | |
| Double side | |
| Time | |
| Temp. demand | |
| Other* | |

EMC

| | |
|-----------|--|
| ES | |
| ES B | |
| PE | |
| PE B | |
| Gasket | |
| Earthbolt | |
| Other* | |

Other* information Cable size/quantity etc



**THORNE &
DERRICK
INTERNATIONAL**

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com