



CMP EXPLOSIVE ATMOSPHERE BARRIER PRODUCTS

PX2KX Ex e Exd ExnR Exta

PX2KX Globally Approved, Explosive Atmosphere Barrier Cable Gland

For all types of Braid & Tape Armoured Cables

- Metal-to-metal armour clamping
- Direct & remote installation
- Compound barrier type flameproof seal
- Controlled outer 'load retention' seal
- Unique OSTG prevents overtightening
- Integral protected deluge seal
- -60°C to +85°C
- Class I Zone 1, 21 and Zone 2, 22 Class I Division 1 & 2 ABCD
- Globally marked, IECEx, ATEX, UL & cCSAus
- EMC tested



† Grooved Cone (X) is predominantly used for Wire Braid (e.g. GSWB, TCWB), Steel Tape Armour (STA, DSTA) and Aluminium Strip Armour (ASA) but is also suitable for Single Wire Armour (SWA), Aluminium Wire Armour (AWA) and Pliable Wire Armour (PWA) if the range is outside that of the Stepped Cone (W).

Note: Grooved Cone (X) dimensions shown in the Cable Gland Selection Table below are for a double wire strand of braid armour cables. Tapes can also be doubled over. For cables that have only a single layer of armour such as SWA the clamping range should be used as shown in the table below.

TECHNICAL DATA	
Design Specification	BS 6121:Part 1:1989, IEC 62444, EN 62444
Mechanical Classifications*	Impact = Level 8, Retention = Class B
Enclosure Protection	IK10 to IEC 62262 (20 joules) Brass & Stainless Steel only
Electrical Classifications*	Category B (Category A when used with braid, tape or pliable wire armour cables)
ATEX Certificate	SIRA13ATEX1072X, SIRA13ATEX4078X
Code of Protection	Ⓢ II 2G, II 1D, Ex d IIC Gb, Ex e IIC Gb, Ex ta IIIC Da, Ⓢ II 3G Ex nR IIC Gc, Ⓢ IM2 Ex d I Mb, Ex e I Mb
Compliance Standards	EN 60079-0,1,7,15,31
IECEx Certificate	IECEx SIR 13.0027X, IECEx SIM 14.0008X
Code of Protection	Ex d IIC Gb, Ex e IIC Gb, Ex nR IIC Gc, Ex ta IIIC Da, Ex d I, Ex e I
Compliance Standards	IEC 60079-0,1,7,15,31
cCSAus Certificate (20s16 - 100)	2288626
CSAus Code of Protection***	Class I, Div. 1, 2 Groups A, B, C and D; Class II, Div. 1, 2 Groups E, F and G; Class III, Div. 1, 2; Type 4X: Oil Resistant II: Class I, Zone 1 AEx d IIC Gb, AEx e IIC Gb, Class I, Zone 2 AEx nR IIC Gc, Class I, Zone 20 AEx ta IIIC Da
cCSA Code of Protection***	Class I, Div. 1, 2 Groups A, B, C and D; Class II, Div. 1, 2 Groups E, F and G; Class III, Div. 1, 2; Type 4X: Oil Resistant II: Ex d IIC Gb, Ex e IIC Gb, Ex nR IIC Gc, Ex ta IIIC Da
Compliance Standards	CAN/CSA-C22.2 No 0,18,25,30,94,174, CAN/CSA-E60079-0,1,7,15,31 CAN/CSA-E61241-1-1 Part 1-1, ANSI/UL 514B Ed 5, ANSI/UL 50 Ed 11, ANSI/UL 2225 Ed 4, UL60079
UL Certificate (20s16 - 100)	E201187, E161256C
Code of Protection	Class I Div 1,2, Groups A,B,C,D, Class II Div 1,2, Groups E,F,G
Compliance Standards	UL 2225, CSA C22.2 No 174, UK 514B, CSA C22.2 No 18, CSA C22.2 No 30
EAC Certificate (Formerly GOST R, K & B)	TC RU C-CB.F605.B00138
UkrSEPRO	UA.TR.047.C.0644-15
KCS Certificate	14-GA4B0-0252X
CCOE / PESO (India) Certificate	P333688
NEPSI Certificate	GYJ13.1140X / GYJ13.1282X
INMETRO Approval	TUV 12.2073X
RETIE Approval Number	03866
Marine Approvals	LR: 01/00172 (E3) DNV: E-13848 ABS: 14-LD234401A-4-PDA, BV: 43180/A1
Ingress Protection Rating	IP66, IP67 & IP68**
Deluge Protection Compliance	DTS01 : 91
Cable Gland Material	Electroless Nickel Plated Brass, Brass, Stainless Steel, Aluminium
Seal Material	CMP SOLO LSF Halogen Free Thermoset Elastomer / Epoxy Barrier Compound
Cable Type	Screened Flexible (EMC) Wire Braid (e.g. CY / SY), Pliable Wire Armour (PWA), Steel Tape Armour (STA), Wire Braid Armour (e.g. SWB), Aluminium Strip Armour (ASA), Armoured & Jacketed***
Armour Clamping	Detachable Compound Tube / Cone & AnyWay Universal Clamping Ring
Sealing Technique	Unique CMP 'LRS' Outer Seal (Load Retention Seal)
Sealing Area(s)	Inner Compound Barrier & Outer Sheath

* Mechanical & Electrical Classifications applied as per IEC 62444 & EN 62444
** Refer to page 7 or www.cmp-products.com for further information on Ingress Protection Ratings
***Where the cable is permitted by code (NEC and/or CEC)

Cable Gland Selection Table

Refer to illustration at the top of the page.

Dimensions listed below are for metric cable glands only
Dimensions for alternative threads may vary, please see supplementary technical data sheet

Cable Gland Size	Available Entry Threads "C" (Alternate Metric Thread Lengths Available)					Number of Cores	Diameter Over Conductors "A"	Cable Bedding Diameter "G"	Overall Cable Diameter "B"		Armour Range † Grooved Cone (X)		Across Flats "D"	Across Corners "D"	Protrusion Length "F"	Combined Ordering Reference ("Brass Metric")			Shroud	Cable Gland Weight (Kgs)	
	Standard		Option						Max	Min	Max	Min				Max	Size	Type			Ordering Suffix
	Metric	Thread Length (Metric) "E"	NPT	Thread Length (NPT) "E"	NPT																
20s16	M20	15.0	1/2"	19.9	3/4"	11	11.7	11.7	6.1	13.1	0.3	1.0	30.5	33.6	62.0	20S16	PX2KX	1RA	PVC06	0.24	
20S	M20	15.0	1/2"	19.9	3/4"	11	11.7	11.7	9.5	15.9	0.3	1.0	30.5	33.6	62.0	20S	PX2KX	1RA	PVC06	0.23	
20	M20	15.0	1/2"	19.9	3/4"	11	12.6	12.9	12.5	20.9	0.4	1.0	30.5	33.6	63.0	20	PX2KX	1RA	PVC06	0.24	
25S	M25	15.0	3/4"	20.2	1"	21	17.5	17.9	14.0	22.0	0.4	1.2	37.5	41.3	69.5	25S	PX2KX	1RA	PVC09	0.37	
25	M25	15.0	3/4"	20.2	1"	21	17.5	17.9	18.2	26.2	0.4	1.2	37.5	41.3	69.5	25	PX2KX	1RA	PVC09	0.37	
32	M32	15.0	1"	25.0	1 1/4"	38	23.6	23.9	23.7	33.9	0.4	1.2	46.0	50.6	75.0	32	PX2KX	1RA	PVC11	0.57	
40	M40	15.0	1 1/4"	25.6	1 1/2"	59	30.0	30.3	27.9	40.4	0.4	1.6	55.0	60.5	75.0	40	PX2KX	1RA	PVC15	0.80	
50S	M50	15.0	1 1/2"	26.1	2"	89	36.6	36.9	35.2	46.7	0.4	1.6	60.0	66.0	77.0	50S	PX2KX	1RA	PVC18	0.90	
50	M50	15.0	2"	26.9	2 1/2"	89	41.0	41.3	40.4	53.0	0.6	1.6	70.0	77.0	77.0	50	PX2KX	1RA	PVC21	1.19	
63S	M63	15.0	2"	26.9	2 1/2"	115	47.9	48.4	45.6	59.4	0.6	1.6	75.0	82.5	79.7	63S	PX2KX	1RA	PVC23	1.39	
63	M63	15.0	2 1/2"	39.9	3"	115	53.7	54.0	54.6	65.8	0.6	1.6	80.0	88.0	80.3	63	PX2KX	1RA	PVC25	1.41	
75S	M75	15.0	2 1/2"	39.9	3"	140	59.9	60.2	59.0	72.0	0.6	1.6	90.0	99.0	86.8	75S	PX2KX	1RA	PVC28	2.09	
75	M75	15.0	3"	41.5	3 1/2"	140	64.2	64.2	66.7	78.4	0.6	1.6	100.0	110.0	88.3	75	PX2KX	1RA	PVC30	2.54	
90	M90	24.0	3 1/2"	42.8	4"	200	75.3	75.6	76.2	90.3	0.8	1.6	115.0	126.5	102.9	90	PX2KX	1RA	PVC32	3.71	
100	M100	24.0	3 1/2"	42.8	4"	200	85.6	85.9	86.1	101.4	0.8	1.6	127.0	139.7	114.0	100	PX2KX	1RA	LSF33	4.31	

*For material options add the following suffix to the Ordering Reference: Brass (no suffix required); Nickel Plated Brass 'S'; 316 Grade Stainless Steel '4'; Copper Free Aluminium '1'
For NPT options please add the following digits to the material suffix; 1/2" = 31, 3/4" = 32, 1" = 33, 1 1/4" = 34, 1 1/2" = 35, 2" = 36, 2 1/2" = 37, 3" = 38, 3 1/2" = 39, 4" = 310 (Brass requires prefix "0")

Examples: 32PX2KX1RA534 = Nickel Plated Brass 1-1/4" NPT, 50SPX2KX1RA035 = Brass 1-1/2" NPT, 25PX2KX1RA432 = Stainless Steel 3/4" NPT, 20PX2KX1RA5 = Nickel Plated Brass M20

Dimensions are displayed in millimetres unless otherwise stated