



Draka



Firetuf FTP – Fire Resistant Armoured Power Cable

Firetuf FTP is the original Draka fire resistant armoured cable and meets the requirements of the construction standard BS7846 with classification F2. The advanced Draka OHLS® characteristics are retained in FTP with halogen free and low smoke properties and also the flame retardant performance that minimises the spread of fire along the cable. FTP holds third party certification by BASEC and LPCB.



Construction

Manufacturing standard:	BS 7846	
Conductors:	Stranded plain annealed copper wire (class 2) to BS EN 60228	
Insulation:	Mica-glass fire resistant tapes, covered by an extruded layer of XLPE	
Binder:	Polyester tape	
Bedding:	Zero Halogen, Low Smoke (OHLS)	
Armour:	Galvanised Steel Wire Armour	
Sheath:	Zero Halogen, Low Smoke (OHLS)	
Core colours:	Harmonised	Non-Harmonised/Middle East
	Two core: Brown and Blue	Red and Black
	Three core: Brown, Black and Grey	Red, Yellow and Blue
	Four core: Brown, Black, Grey and Blue	Black, Red, Yellow and Blue
Sheath colour:	Black (Other colours available on request)	

Physical Characteristics

Voltage rating (U_o/U):	600/1000V.
Operating temp:	-25°C to +90°C (the cable should not be installed when either the ambient or cable temperature is below 0°C)
Min, bending radius:	8 x overall diameter
Curent rating:	Refer to tables 4E4A & 4E4B in BS7671 or ERA 69-30 Part V

Note: In the event of a fire, the increase in impedance may require consideration to the installation of larger conductor sizes, to accommodate motor starting loads and the performance of protective conductors

Performance characteristics

Circuit integrity:	BS 6387 categories C, W & Z BS 7846 F2
Smoke emission:	BS EN 61034-2
Acid gas emmision:	BS EN 50267-2-1
Flame propagation:	BS EN 60332-1-2 BS EN 60332-3-24



THORNE &
DERRICK
INTERNATIONAL

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com

A brand of the
Prysmian
Group



Draka



2 Core 2FTP2H

Nominal area of conductor	Armour wire diameter	Approx. diameter under armour	Approx. overall diameter	Approx. cable weight	Maximum conductor resistance		Nominal area of armour	Maximum armour resistance at 20°C
					DC at 20°C Ω/km	AC at 90°C Ω/km		
mm ²	mm	mm	mm	kg/km			mm ²	Ω/km
1.5*	0.9	8.8	12.9	340	12.1	15.428	15	10.2
2.5*	0.9	9.8	14.1	400	7.41	9.448	17	8.8
4*	0.9	10.7	15.0	465	4.61	5.878	19	7.9
6*	0.9	12.0	16.3	555	3.08	3.927	22	7
10*	0.9	14.2	18.8	750	1.83	2.333	26	6
16*	1.25	15.5	20.7	1015	1.15	1.466	42	3.7
25*	1.25	19.1	24.5	1415	0.727	0.926	42	3.7
35*	1.6	21.4	27.7	1895	0.524	0.6685	60	2.6
50	1.6	21.1	27.7	1955	0.387	0.494	68	2.3
70	1.6	24.1	31.0	2515	0.268	0.3412	80	2
95	2.0	25.3	32.8	3225	0.193	0.2471	113	1.4
120	2.0	28.9	36.4	3900	0.153	0.1964	125	1.3
150	2.0	31.2	39.1	4575	0.124	0.1597	138	1.2
185	2.5	34.7	43.9	5890	0.0991	0.1284	191	0.82
240	2.5	39.4	48.7	7275	0.0754	0.0989	215	0.73
300	2.5	43.8	53.4	8825	0.0601	0.0801	235	0.67
400	2.5	48.6	58.5	10725	0.047	0.0641	265	0.59

3 Core 2FTP3H

Nominal area of conductor	Armour wire diameter	Approx. diameter under armour	Approx. overall diameter	Approx. cable weight	Maximum conductor resistance		Nominal area of armour	Maximum armour resistance at 20°C
					DC at 20°C Ω/km	AC at 90°C Ω/km		
mm ²	mm	mm	mm	kg/km			mm ²	Ω/km
1.5*	0.9	9.3	13.4	365	12.1	15.428	16	9.5
2.5*	0.9	10.4	14.7	440	7.41	9.448	19	8.2
4*	0.9	11.4	15.7	515	4.61	5.878	20	7.5
6*	0.9	12.8	17.1	630	3.08	3.927	23	6.7
10*	1.25	15.2	20.4	985	1.83	2.333	39	4
16*	1.25	16.5	21.9	1200	1.15	1.466	45	3.5
25*	1.6	20.6	26.9	1855	0.727	0.926	62	2.5
35*	1.6	22.9	29.4	2265	0.524	0.6685	68	2.3
50	1.6	23.6	30.3	2525	0.387	0.494	78	2
70	1.6	26.8	33.7	3280	0.268	0.3412	90	1.8
95	2.0	30.0	37.6	4360	0.193	0.2471	128	1.3
120	2.0	33.1	40.9	5230	0.153	0.1964	141	1.2
150	2.5	37.0	46.0	6650	0.124	0.1597	201	0.78
185	2.5	40.8	49.9	7920	0.0991	0.1284	220	0.71
240	2.5	45.6	55.2	9950	0.0754	0.0989	250	0.63
300	2.5	50.5	60.3	12020	0.0601	0.0801	269	0.58
400	2.5	56.3	66.4	14805	0.047	0.0641	304	0.52



A brand of the

Prysmian
Group



4 Core 2FTP4H

Nominal area of conductor	Armour wire diameter	Approx. diameter under armour	Approx. overall diameter	Approx. cable weight	Maximum conductor resistance		Nominal area of armour	Maximum armour resistance at 20°C
					DC at 20°C Ω/km	AC at 90°C Ω/km		
mm ²	mm	mm	mm	kg/km			mm ²	Ω/km
1.5*	0.9	10.4	14.5	420	12.1	15.428	17	8.8
2.5*	0.9	11.6	15.9	510	7.41	9.448	20	7.7
4*	0.9	12.7	17.1	605	4.61	5.878	22	6.8
6*	1.25	14.3	19.5	860	3.08	3.927	36	4.3
10*	1.25	16.7	21.9	1135	1.83	2.333	42	3.7
16*	1.25	18.2	23.6	1415	1.15	1.466	50	3.1
25*	1.6	22.8	29.0	2190	0.727	0.926	70	2.3
35*	1.6	25.3	31.8	2700	0.524	0.6685	78	2
50	1.6	27.0	33.9	3145	0.387	0.494	90	1.8
70	2.0	30.3	38.0	4295	0.268	0.3412	131	1.2
95	2.0	33.8	41.7	5455	0.193	0.2471	147	1.1
120	2.5	37.8	46.8	7010	0.153	0.1964	206	0.76
150	2.5	41.9	51.1	8335	0.124	0.1597	230	0.68
185	2.5	46.7	56.3	10095	0.0991	0.1284	255	0.61
240	2.5	52.2	61.9	12655	0.0754	0.0989	289	0.54
300	2.5	57.3	67.3	15320	0.0601	0.0801	319	0.49
400	3.15	64.2	76.0	19810	0.047	0.0641	452	0.35



**THORNE &
DERRICK**
INTERNATIONAL

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com