



Draka

FTP120

FIRETUF®

Firetuf FTP 120 - Fire Resistant Armoured Power Cable

Draka Firetuf FTP120 is a fire resistant armoured power cable solution for all three categories of fire performance required by BS8519, Category 1,2 and 3. FTP120 is third party approved by LPCB for 120 min classification in BS8491. This is the test for fire resistance that includes direct flame, direct impact and water jet at 850°C. FTP120 holds third party BASEC certification to BS7846, the construction requirements for fire resistant armoured cables. LU approved cable (LU Approval ref 406).



Construction

Manufacturing standard:	BS 7846	
Conductors:	Stranded plain annealed copper wire (Class 2) to BS EN 60228	
Insulation:	Mica-glass fire resistant tapes, covered by an extruded layer of XLPE	
Binder:	Polyester tape, glass tapes where performance requires	
Bedding:	Zero Halogen, Low Smoke (OHLS®)	
Armour:	Galvanised Steel Wire Armour	
Sheath:	Zero Halogen, Low Smoke (OHLS®)	
Core colours:	Harmonised	Non-Harmonised/Middle East
	Two core: Brown and Blue	Red and Black
	Three core: Brown, Black and Grey	Red, Yellow and Blue
	Four core: Brown, Black, Grey and Blue	Black, Red, Yellow and Blue
Sheath colour:	Black (Other colours available on request)	

Physical Characteristics

Voltage rating (U₀/U):	600/1000V
Operating temp:	-25°C to +90°C (the cable should not be installed when either the ambient or cable temperature is below 0°C)
Min, bending radius:	8 x overall diameter of cable
Current rating:	Refer to tables 4E4A & 4E4B in BS7671 or ERA 69-30 Part V

Note: In the event of a fire, the increase in impedance may require consideration to the installation of larger conductor sizes, to accommodate motor starting loads and the performance of protective conductors.

Performance Characteristics

Circuit integrity:	BS 7846 F120 BS 8491 30, 60 and 120mins
Smoke emission:	BS EN 61034-2
Acid gas emission:	BS EN 50267-2-1
Flame propagation:	BS EN 60332-1-2 BS EN 60332-3-24



THORNE &
DERRICK
INTERNATIONAL

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com

A brand of the
Prysmian
Group



Draka

FtP120 FIRETUF®

2 Core FTTP2H

Nominal area of conductor	Armour wire diameter	Approx. diameter under armour	Approx. overall diameter	Approx. cable weight	Maximum conductor resistance		Nominal area of armour	Maximum armour resistance at 20°C
					DC at 20 C Ω/km	AC at 90 C Ω/km		
mm ²	mm	mm	mm	kg/km			mm ²	Ω/km
4*	1.25	14.7	20.2	765	4.61	5.878	19	7.9
6*	1.25	14.7	20.2	760	3.08	3.927	22	7
10*	1.25	15.9	21.7	875	1.83	2.333	26	6
16*	1.25	17.2	22.9	1020	1.15	1.466	42	3.7
25*	1.25	20.2	26.1	1325	0.727	0.926	42	3.7
35*	1.6	22.5	29.3	1820	0.524	0.6685	60	2.6
50	1.6	23.5	29.5	2580	0.387	0.494	68	2.3
70	1.6	25.5	33.0	2045	0.268	0.3412	80	2
95	2.0	26.7	34.9	3465	0.193	0.2471	113	1.4
120	2.0	30.1	38.5	4150	0.153	0.1964	125	1.3
150	2.0	32.6	41.1	4845	0.124	0.1597	138	1.2
185	2.5	36.1	46.0	6235	0.0991	0.1284	191	0.82
240	2.5	40.7	50.8	7635	0.0754	0.0989	215	0.73
300	2.5	44.6	54.9	9155	0.0601	0.0801	235	0.67
400	2.5	49.8	60.4	11140	0.047	0.0641	265	0.59

3 Core FTTP3H

Nominal area of conductor	Armour wire diameter	Approx. diameter under armour	Approx. overall diameter	Approx. cable weight	Maximum conductor resistance		Nominal area of armour	Maximum armour resistance at 20°C
					DC at 20 C Ω/km	AC at 90 C Ω/km		
mm ²	mm	mm	mm	kg/km			mm ²	Ω/km
4*	1.25	14.7	20.2	785	4.61	5.878	20	7.5
6*	1.25	14.8	20.3	795	3.08	3.927	23	6.7
10*	1.25	17.0	22.7	1020	1.83	2.333	39	4
16*	1.25	18.3	24.2	1230	1.15	1.466	45	3.5
25*	1.6	21.8	28.5	1795	0.727	0.926	62	2.5
35*	1.6	24.0	31.0	2170	0.524	0.6685	68	2.3
50	1.6	25.1	32.1	2615	0.387	0.494	78	2
70	1.6	28.2	35.4	3360	0.268	0.3412	90	1.8
95	2.0	31.4	39.8	4605	0.193	0.2471	128	1.3
120	2.0	34.5	43.1	5505	0.153	0.1964	141	1.2
150	2.5	38.4	48.1	7010	0.124	0.1597	201	0.78
185	2.5	42.2	52.1	8295	0.0991	0.1284	220	0.71
240	2.5	46.9	57.1	10330	0.0754	0.0989	250	0.63
300	2.5	51.8	62.3	14425	0.0601	0.0801	269	0.58
400	2.5	57.6	68.4	15270	0.047	0.0641	304	0.52

4 Core FTTP4H

Nominal area of conductor	Armour wire diameter	Approx. diameter under armour	Approx. overall diameter	Approx. cable weight	Maximum conductor resistance		Nominal area of armour	Maximum armour resistance at 20°C
					DC at 20°C Ω/km	AC at 90°C Ω/km		
mm ²	mm	mm	mm	kg/km			mm ²	Ω/km
4*	1.25	15.0	20.5	795	4.61	5.878	22	6.8
6*	1.25	16.2	22.0	930	3.08	3.927	36	4.3
10*	1.25	18.7	24.4	1200	1.83	2.333	42	3.7
16*	1.25	20.2	26.1	1460	1.15	1.466	50	3.1
25*	1.6	24.0	30.8	2150	0.727	0.926	70	2.3
35*	1.6	26.6	33.6	2635	0.524	0.6685	78	2
50	1.6	29.0	36.2	3275	0.387	0.494	90	1.8
70	2.0	31.9	40.2	4555	0.268	0.3412	131	1.2
95	2.0	35.4	43.9	5770	0.193	0.2471	147	1.1
120	2.5	39.4	49.1	7380	0.153	0.1964	206	0.76
150	2.5	43.3	53.2	8720	0.124	0.1597	230	0.68
185	2.5	48.1	58.4	10535	0.0991	0.1284	255	0.61
240	2.5	53.6	64.0	13115	0.0754	0.0989	289	0.54
300	2.5	58.7	69.4	15805	0.0601	0.0801	319	0.49
400	3.15	65.6	78.1	20420	0.047	0.0641	452	0.35

*Circular conductors, all others are shaped conductors



THORNE &
DERRICK
INTERNATIONAL

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com

A brand of the
Prysmian
Group