



E1W SOLO

E1W Industrial Double Seal Cable Gland SOLO LSF Kit

For all types of Steel & Aluminium Wire Armoured Cables

- Metal-to-metal armour clamping
- Direct & remote installation
- Displacement type inner seal
- Controlled outer 'load retention' seal
- Unique OSTG prevents overtightening
- Deluge protection option
- -60°C to +130°C
- EMC tested
- LUL (London Underground) approved



Note: Ordering suffix '2RA' includes locknut, earth tag & shroud
Other kit options available



Gland Kit shown as example

TECHNICAL DATA

Type	E1W SOLO-Kit
Design Specification	BS 6121:Part 1:1989, IEC 62444, EN 62444
Mechanical Classifications*	Impact = Level 8, Retention = Class D
Enclosure Protection	IK10 to IEC 62262 (20 joules) Brass & Stainless Steel only
Electrical Classifications*	Category B
GOST R Certificate Number	POCC GB. ГБ05.H00187
GOST K Certificate Number	KZ 7500361.01.01.25266
RoK Permit For Use Number	19-02-UL-1957
Marine Approvals	LRS: 01/00171 (E1), ABS: 01-LD234401/2-PDA
Ingress Protection Rating	IP66 as standard (IP67, IP68 available upon request)**
Cable Gland Material	Brass, Electroless Nickel Plated Brass, Aluminium
Seal Material	CMP SOLO LSF Halogen Free Thermoset Elastomer
Cable Type	Single Wire Armour (SWA), Aluminium Wire Armour (AWA)
Armour Clamping	Detachable Armour Cone & AnyWay Universal Clamping Ring
Sealing Technique	CMP Inner Displacement Seal & Unique CMP 'LRS'™ Outer Load Retention Seal
Sealing Area(s)	Cable Inner Bedding & Outer Cable Sheath
Cable Gland Kits Available	Up to & including size 25 - 2 glands, 2 locknuts, 2 earth tags & 2 LSF shrouds Size 32 & above - 1 gland, 1 locknut, 1 earth tag & 1 LSF shroud

Note : * Mechanical & Electrical Classifications applied as per IEC 62444 & EN 62444

Note : ** Refer to page 7 or www.cmp-products.com for further information on Ingress Protection Ratings

Cable Gland Selection Table

Refer to illustration at the top of the page

Cable Gland Size	Available Entry Threads "C" (Alternate Metric Thread Lengths Available)					Cable Bedding Diameter "A"		Overall Cable Diameter "B"		Armour Range		Across Flats "D"	Across Corners "D"	Protrusion Length "F" (Without Shroud)	Combined Ordering Reference (*Brass Metric)			Cable Gland Only Weight (Kgs)
	Standard				Option	Min	Max	Min	Max	Min	Max	Max	Max		Size	Type	Ordering Suffix	
	Metric	Thread Length (Metric) "E"	NPT	Thread Length (Metric) "E"	NPT													
20s16	M20	10.0	1/2"	19.9	3/4"	3.1	8.6	6.1	13.1	0.8	1.25	24.0	26.4	72.5	20S16	E1WLSF	2RA	0.163
20S	M20	10.0	1/2"	19.9	3/4"	6.1	11.6	9.5	15.9	0.8	1.25	24.0	26.4	70.0	20S	E1WLSF	2RA	0.150
20	M20	10.0	1/2"	19.9	3/4"	6.5	13.9	12.5	20.9	0.8	1.25	30.5	33.6	73.0	20	E1WLSF	2RA	0.210
25S	M25	10.0	3/4"	20.2	1"	11.1	19.9	14.0	22.0	1.25	1.6	37.5	41.3	89.0	25S	E1WLSF	2RA	0.330
25	M25	10.0	3/4"	20.2	1"	11.1	19.9	18.2	26.2	1.25	1.6	37.5	41.3	89.0	25	E1WLSF	2RA	0.330
32	M32	10.0	1"	25.0	1 1/4"	17.0	26.2	23.7	33.9	1.6	2.0	46.0	50.6	86.0	32	E1WLSF	2RA	0.430
40	M40	15.0	1 1/4"	25.6	1 1/2"	22.0	32.1	27.9	40.4	1.6	2.0	55.0	60.5	90.0	40	E1WLSF	2RA	0.620
50S	M50	15.0	1 1/2"	26.1	2"	29.5	38.1	35.2	46.7	2.0	2.5	60.0	66.0	91.0	50S	E1WLSF	2RA	0.750
50	M50	15.0	2"	26.9	2 1/2"	35.6	44.0	40.4	53.0	2.0	2.5	70.1	77.1	95.0	50	E1WLSF	2RA	0.950
63S	M63	15.0	2"	26.9	2 1/2"	40.1	49.9	45.6	59.4	2.0	2.5	75.0	82.5	102.0	63S	E1WLSF	2RA	1.340
63	M63	15.0	2 1/2"	39.9	3"	47.2	55.9	54.6	65.8	2.0	2.5	80.0	88.0	104.0	63	E1WLSF	2RA	1.340
75S	M75	15.0	2 1/2"	39.9	3"	52.8	61.9	59.0	72.0	2.0	2.5	90.0	99.0	115.0	75S	E1WLSF	2RA	2.110
75	M75	15.0	3"	41.5	3 1/2"	59.1	67.9	66.7	78.4	2.5	3.0	100.0	110.0	117.0	75	E1WLSF	2RA	2.420
90	M90	24.0	3 1/2"	42.8	4"	66.6	78.6	76.2	90.3	3.15	4.0	114.3	125.4	147.0	90	E1WLSF	2RA	4.210
100	M100	24.0	4"	44.0	5"	76.0	90.9	86.1	101.4	3.15	4.0	123.0	135.3	140.0	100	E1WLSF	2RA	4.450
115	M115	24.0	4"	44.0	5"	86.0	97.9	101.5	110.2	3.15	4.0	133.4	146.7	162.0	115	E1WLSF	2RA	6.190
130	M130	24.0	5"	46.8	6"	97.0	114.9	110.2	123.2	3.15	4.0	152.4	167.6	174.0	130	E1WLSF	2RA	8.340

*For material options add the following suffix to the Ordering Reference; Brass (no suffix required); Nickel Plated Brass '5'; 316 Grade Stainless Steel '4'; Copper Free Aluminium '1'
For NPT options add the following digits to the material suffix; 1/2" = 31; 3/4" = 32; 1" = 33; 1 1/4" = 34; 1 1/2" = 35; 2" = 36; 2 1/2" = 37; 3" = 38; 3 1/2" = 39; 4" = 310 (Brass requires prefix '0')

Examples: 32E1WLSF2RA5 = Nickel Plated Brass, 32E1WLSF2RA1 = Copper Free Aluminium, 20E1WLSF2RA5 = Nickel Plated Brass M20

Dimensions are displayed in millimetres unless otherwise stated

