

## NA2XS(F)2Y RM 12/20 kV

Single-core XLPE-insulated cables with PE sheath, longitudinally watertight

### Description

#### Construction

stranded aluminium conductor - conductor screen of semiconducting compound - insulation of cross-linked polyethylen (XLPE) - screen of semiconducting compound - semiconducting swellable tape - screen of copper wires and copper tape - separation tape - PE sheath.

On request we are also delivering the construction with inner rubber sheath.

#### Application

in ground, outdoors, in water, indoors and in cable ducts

This product is also part of our Windlink® offer dedicated to wind turbines.

#### Packaging

on request



#### Standards

International IEC 60502-2

### Characteristics

Construction characteristics	
Conductor shape	Circular stranded (RM)
Lead free	Yes
Halogen free	Yes
Insulation	XLPE (chemical)
Material of bedding	SC swelling tape
Screen	Copper wire + copper tape
Outer sheath	PE
Longitudinally watertight	Yes
Sheath colour	Black
Usage characteristics	
Minimum installation temperature	-20 °C
Minimum operating temperature	-40 °C
Max. conductor temperature in service	90 °C
Short-circuit max. conductor temperature	250 °C
Bending factor when laying	15 (xD)



Lead free  
Yes



Halogen free  
Yes



Longitudinally  
watertight  
Yes



Minimum installation  
temperature  
-20 °C



Minimum operating  
temperature  
-40 °C



Max. conductor  
temperature in service  
90 °C



Bending factor  
when laying  
15 (xD)

**Contact**

Cables for Energy Networks  
Phone: 01908 250839  
[sales.energynetworks@nexans.com](mailto:sales.energynetworks@nexans.com)

## NA2XS(F)2Y RM 12/20 kV

### Selling information

Note: On request we are delivering three single core laid up cables on one drum



Lead free  
Yes



Halogen free  
Yes



Longitudinally  
watertight  
Yes



Minimum installation  
temperature  
-20 °C



Minimum operating  
temperature  
-40 °C



Max. conductor  
temperature in service  
90 °C



Bending factor  
when laying  
15 (xD)



THORNE &  
**DERRICK**  
INTERNATIONAL

**Thorne & Derrick**  
+44 (0) 191 410 4292  
[www.powerandcables.com](http://www.powerandcables.com)