



Arc Flash equipment

"Arc flash" protective kits
(25, 40, 65 or 100 cal/cm²)



Reference	Capacity cal/cm ²	kg	Color
KIT-ARC-25-B-(*) *1	25	6	KAKI
KIT-ARC-40-B-(*) *2	40	6.9	GREY
KIT-ARC-65-B-(*) *3	65	8	CAMEL
KIT-ARC-100-B-(*) *4	100	8	CAMEL

Composition of KITS

M-881968 *1 M-881961 *2 M-881976 *3 M-881979 *4	1 arc flash protective hood with an integrated face shield 25 *1, 40 *2, 65 *3 or 100 *4 cal/cm ² , ASTM F2178 and NFPA 70E Standards
MO-182/1-B	1 ABS helmet electrically insulated EN397, EN 50365, ANSI Z89.1 20kV.
—	1 arc flash protective bib overall 25 *1, 40 *2, 65 *3 or 100 *4 cal/cm ² , ASTM F1506 and NFPA 70E Standards
—	1 arc flash protective coat 25 *1, 40 *2, 65 *3 or 100 *4 cal/cm ² , ASTM F1506 and NFPA 70E Standards
MO-11000	1 safety glasses EN 166/EN 170
M-87295	1 all kit carrying bag



Arc Flash protective hood with face shield, 40 cal/cm².

Electrician helmet.

(*) Reference to be completed by the size M, L or XL. Size S to 3 XL on request.

1 For reference KIT-ARC-25-B-()

2 For reference KIT-ARC-40-B-()

3 For reference KIT-ARC-65-B-()

4 For reference KIT-ARC-100-B-()



KIT-ARC-25-B-(*)

KIT-ARC-40-B-(*)

KIT-ARC-65/100-B-(*)