

‘C’ Crimp Connectors

These range-taking ‘C’ Crimp Connectors are specifically designed for tap and parallel connections of stranded copper cables in earthing applications.



CCC 035



CCC 070



CCC 240

Main Conductor A mm ²	Tap Conductor B mm ²	L mm	W mm	H mm	Unit Weight kg	Pack Quantity	Part Number
10	4 - 10	12	9	13	0.01	100	CCC 010
10 - 16	10 - 16	17	12	19	0.01	100	CCC 016
16	4	17	12	19	0.01	100	CCC 016
16 - 25	1.5 - 10	12	13	20	0.02	100	CCC 25-10
25	10 - 16	19	12	21	0.02	50	CCC 25PM
25	10 - 25	20	15	24	0.04	50	CCC 025
35	1.5 - 16	20	15	24	0.04	50	CCC 025
35	25 - 35	20	15	27	0.05	50	CCC 035
50	4 - 16	20	15	27	0.05	50	CCC 035
50	16 - 50	20	17	27	0.07	50	CCC 050
70	1.5 - 25	20	17	27	0.07	25	CCC 050
50 - 70	4 - 35	28	21	33	0.09	25	CCC 70-35
50 - 70	35 - 70	28	21	34	0.10	25	CCC 070
70 - 95	35 - 70	30	26	41	0.10	25	CCC 075
95	4 - 35	30	26	41	0.11	25	CCC 95-35
70 - 95	95	30	26	41	0.12	25	CCC 095
120	35 - 120	30	28	45	0.12	25	CCC 120
150	6 - 70	30	28	45	0.12	25	CCC 120
150	95 - 150	30	28	45	0.15	10	CCC 150
120 - 185	95 - 185	35	33	54	0.20	10	CCC 185
150 - 185	70 - 150	35	33	54	0.20	10	CCC 185
240	95 - 120	37	34	54	0.24	10	CCC 240-120
240	150 - 240	40	34	54	0.24	10	CCC 240

Material: Copper.

