

## Earth Rod to Tape 'A' Clamps

These clamps are used for joining earth rods to different sizes of copper tape. The clamps have a high resistance to corrosion and are mechanically strong to ensure a lasting connection.

| Earth Rod Shank Ø mm | Maximum Tape Size mm | L mm | W mm | H mm | Unit Weight kg | Pack Quantity | Part Number |
|----------------------|----------------------|------|------|------|----------------|---------------|-------------|
| 12.7                 | 26 x 15              | 43   | 37   | 17   | 0.10           | 50            | ERA 1625    |
|                      | 32 x 15              | 43   | 45   | 18   | 0.20           | 25            | ERA 1631    |
|                      | 39 x 15              | 44   | 51   | 22   | 0.25           | 25            | ERA 1638    |
| 14.2                 | 26 x 14              | 43   | 37   | 17   | 0.10           | 50            | ERA 1625    |
|                      | 32 x 14              | 43   | 45   | 18   | 0.20           | 25            | ERA 1631    |
|                      | 39 x 14              | 44   | 51   | 22   | 0.25           | 25            | ERA 1638    |
|                      | 51 x 16              | 47   | 64   | 20   | 0.21           | 25            | ERA 1650    |
| 15.0                 | 26 x 13              | 43   | 37   | 17   | 0.10           | 50            | ERA 1625    |
|                      | 32 x 13              | 43   | 45   | 18   | 0.20           | 25            | ERA 1631    |
|                      | 39 x 13              | 44   | 51   | 22   | 0.25           | 25            | ERA 1638    |
|                      | 51 x 15              | 47   | 64   | 20   | 0.21           | 25            | ERA 1650    |
| 16.0                 | 26 x 12              | 43   | 37   | 17   | 0.10           | 50            | ERA 1625    |
|                      | 32 x 12              | 43   | 45   | 18   | 0.20           | 25            | ERA 1631    |
|                      | 39 x 12              | 44   | 51   | 22   | 0.25           | 25            | ERA 1638    |
|                      | 51 x 14              | 47   | 64   | 20   | 0.21           | 25            | ERA 1650    |
| 17.2                 | 26 x 11              | 43   | 37   | 17   | 0.10           | 50            | ERA 1625    |
|                      | 32 x 11              | 43   | 45   | 18   | 0.20           | 25            | ERA 1631    |
|                      | 39 x 11              | 44   | 51   | 22   | 0.25           | 25            | ERA 1638    |
|                      | 51 x 13              | 47   | 64   | 20   | 0.21           | 25            | ERA 1650    |
|                      | 26 x 18              | 55   | 40   | 25   | 0.20           | 10            | ERA 2525    |
| 20.0                 | 26 x 8               | 43   | 37   | 17   | 0.10           | 50            | ERA 1625    |
|                      | 32 x 8               | 43   | 45   | 18   | 0.20           | 25            | ERA 1631    |
|                      | 39 x 8               | 44   | 51   | 22   | 0.25           | 25            | ERA 1638    |
|                      | 51 x 10              | 47   | 64   | 20   | 0.21           | 25            | ERA 1650    |
|                      | 26 x 16              | 55   | 40   | 25   | 0.20           | 10            | ERA 2525    |
| 25.0                 | 26 x 11              | 55   | 40   | 25   | 0.20           | 10            | ERA 2525    |

**Material:** Aluminium Bronze with M10 x 25mm Phosphor Bronze Set Screw.

The aluminium version is mainly used for connecting aluminium tape to a puddle flange rod as part of a lightning protection system.

| Rod Shank Ø mm | Maximum Tape Size mm | L mm | W mm | H mm | Unit Weight kg | Pack Quantity | Part Number |
|----------------|----------------------|------|------|------|----------------|---------------|-------------|
| 16.0           | 26 x 12              | 44   | 40   | 19   | 0.60           | 25            | ERA 1625A   |

**Material:** Aluminium with M10 x 25mm Stainless Steel Set Screw.

