

SICON bolted cable lug 50-240 mm²

The special design of SICON bolts means that there are no fixed predetermined break points in the thread. Instead the bolt always breaks reliably at the surface of the clamp body.

- Nothing protrudes from the clamp body
- Full use of the thread load rating for any conductor cross section
- No special tools needed
- Smooth breakage of the shear bolt simplifies tightening



Picture may vary.

Technical Data

Article no.		332 595 010
Conductor cross section Al solid circular	(mm ²)	50 - 240
Conductor cross section Al stranded circular	(mm ²)	50 - 185
Conductor cross section Al stranded circular compressed	(mm ²)	50 - 240
Conductor cross section Al solid sector-shaped	(mm ²)	50 - 185
Conductor cross section Al stranded sector-shaped	(mm ²)	50 - 150
Conductor cross section Cu solid circular	(mm ²)	50 - 240
Conductor cross section Cu stranded circular	(mm ²)	50 - 185
Conductor cross section Cu stranded circular compressed	(mm ²)	50 - 240
Conductor cross section Cu stranded sector-shaped	(mm ²)	50 - 150
Number of screws		2
Mounting hole	Ø (mm)	13
Width across flats		SW 6

Dimensions

Diameter D1	Ø d1 (mm)	33
Diameter D2	Ø d2 (mm)	20
Dimension L1	L ₁ (mm)	115
Dimension L2	L ₂ (mm)	117

