

SICON connector 25-150 mm² with blind hole

The special design of SICON bolts means that there are no fixed predetermined break points in the thread. Instead the bolt always breaks reliably at the surface of the clamp body.

- Nothing protrudes from the clamp body
- Full use of the thread load rating for any conductor cross section
- No special tools needed
- Smooth breakage of the shear bolt simplifies tightening



Picture may vary.

Technical Data

Article no.	332 607 010	
Conductor cross section Al solid circular	(mm ²)	25 - 150
Conductor cross section Al stranded circular	(mm ²)	25 - 150
Conductor cross section Al stranded circular compressed	(mm ²)	25 - 150
Conductor cross section Al solid sector-shaped	(mm ²)	35 - 120
Conductor cross section Al stranded sector-shaped	(mm ²)	35 - 120
Conductor cross section Cu solid circular	(mm ²)	25 - 150
Conductor cross section Cu stranded circular	(mm ²)	25 - 150
Conductor cross section Cu stranded circular compressed	(mm ²)	25 - 150
Conductor cross section Cu stranded sector-shaped	(mm ²)	35 - 120
Stripping length with centring sleeve	(mm)	60
Stripping length without centring sleeve	(mm)	55
Number of screws		2
Width across flats		SW 5

Dimensions

Diameter D1	Ø d1 (mm)	28
Diameter D2	Ø d2 (mm)	16,3
Dimension L1	L ₁ (mm)	68
Dimension L2	L ₂ (mm)	78

