

## SE TYPE - SINGLE EYE CABLE GRIP



Ideal for pulling light to medium loads; typical application - 'standard pull' of single or group of cables, where additional support is unnecessary, or if used in conjunction with other cable grips.

| Slingco Part No                                       | Range       |         | Lattice Weave | Lattice Length |     | Overall Length |     | Approx. Break Load |       |
|---|-------------|---------|---------------|----------------|-----|----------------|-----|--------------------|-------|
|   | in          | mm      |               | in             | mm  | in             | mm  | lb                 | kg    |
| <b>SINGLE EYE STANDARD GRIP - GALVANISED</b>          |             |         |               |                |     |                |     |                    |       |
| ZCS0320   | 0.25 - 0.50 | 10-13   | Single        | 9              | 230 | 12             | 305 | 1,680              | 760   |
| ZCS0321   | 0.50 - 0.75 | 13-19   | Single        | 14             | 355 | 17             | 430 | 2,240              | 1,015 |
| ZCS0322   | 0.75 - 1.00 | 19-25   | Single        | 16             | 405 | 20             | 510 | 5,600              | 2,540 |
| ZCS0323   | 1.00 - 1.50 | 25-38   | Single        | 18             | 455 | 24             | 610 | 7,840              | 3,555 |
| ZCS0324   | 1.50 - 2.00 | 38-50   | Double        | 21             | 535 | 29             | 735 | 11,200             | 5,080 |
| ZCS0325   | 2.00 - 2.50 | 50-63   | Double        | 24             | 610 | 34             | 865 | 11,200             | 5,080 |
| ZCS0326   | 2.50 - 3.50 | 63-89   | Double        | 27             | 685 | 39             | 990 | 13,440             | 6,095 |
| ZCS0327   | 3.50 - 4.50 | 89-115  | Double        | 27             | 685 | 39             | 990 | 15,680             | 7,110 |
| ZCS0821   | 4.50 - 5.50 | 115-140 | Double        | 27             | 685 | 39             | 990 | 15,680             | 7,110 |
| <b>SINGLE EYE STANDARD GRIP - 316 STAINLESS STEEL</b> |             |         |               |                |     |                |     |                    |       |
| ZCS1380   | 0.25 - 0.50 | 10-13   | Single        | 9              | 230 | 12             | 305 | 1,344              | 610   |
| ZCS1523   | 0.50 - 0.75 | 13-19   | Single        | 14             | 355 | 17             | 430 | 1,792              | 810   |
| ZCS1373   | 0.75 - 1.00 | 19-25   | Single        | 16             | 405 | 20             | 510 | 4,480              | 2,030 |
| ZCS1952   | 1.00 - 1.50 | 25-38   | Single        | 18             | 455 | 24             | 610 | 6,272              | 2,845 |
| ZCS1381   | 1.50 - 2.00 | 38-50   | Double        | 21             | 535 | 29             | 735 | 8,960              | 4,065 |
| ZCS1977   | 2.00 - 2.50 | 50-63   | Double        | 24             | 610 | 34             | 865 | 8,960              | 4,065 |
| ZCS1979   | 2.50 - 3.50 | 63-89   | Double        | 27             | 685 | 39             | 990 | 10,752             | 4,875 |
| ZCS1980   | 3.50 - 4.50 | 89-115  | Double        | 27             | 685 | 39             | 990 | 12,544             | 5,690 |
| ZCS1981   | 4.50 - 5.50 | 115-140 | Double        | 27             | 685 | 39             | 990 | 12,544             | 5,690 |

## OS TYPE - OFFSET EYE CABLE GRIP



Similar to the SE Type single eye cable grip, but for when offset positioning is required.

| Slingco Part No                                       | Range       |         | Lattice Weave | Lattice Length |       | Overall Length |       | Approx. Break Load |       |
|---|-------------|---------|---------------|----------------|-------|----------------|-------|--------------------|-------|
|   | in          | mm      |               | in             | mm    | in             | mm    | lb                 | kg    |
| <b>OFFSET EYE STANDARD GRIP - GALVANISED</b>          |             |         |               |                |       |                |       |                    |       |
| ZCS1860   | 0.25 - 0.50 | 10-13   | Single        | 9              | 230   | 12             | 305   | 1,680              | 760   |
| ZCS1861   | 0.50 - 0.75 | 13-19   | Single        | 14             | 355   | 17             | 430   | 2,240              | 1,015 |
| ZCS1862   | 0.75 - 1.00 | 19-25   | Single        | 16             | 405   | 20             | 510   | 5,600              | 2,540 |
| ZCS1863   | 1.00 - 1.50 | 25-38   | Single        | 18             | 455   | 24             | 610   | 7,840              | 3,555 |
| ZCS1864   | 1.50 - 2.00 | 38-50   | Double        | 21             | 535   | 29             | 735   | 11,200             | 5,080 |
| ZCS1865   | 2.00 - 2.50 | 50-63   | Double        | 24             | 610   | 34             | 865   | 11,200             | 5,080 |
| ZCS1866   | 2.50 - 3.50 | 63-89   | Double        | 27             | 685   | 39             | 990   | 13,440             | 6,095 |
| ZCS1867   | 3.50 - 4.50 | 89-115  | Double        | 27             | 685   | 39             | 990   | 15,680             | 7,110 |
| ZCS1974   | 4.50 - 5.50 | 115-140 | Double        | 27             | 685   | 39             | 990   | 15,680             | 7,110 |
| <b>OFFSET EYE STANDARD GRIP - 316 STAINLESS STEEL</b> |             |         |               |                |       |                |       |                    |       |
| ZCS1986   | 0.25 - 0.50 | 10-13   | Single        | 9              | 230   | 12             | 305   | 1,344              | 610   |
| ZCS1987   | 0.50 - 0.75 | 13-19   | Single        | 14             | 355   | 17             | 430   | 1,792              | 810   |
| ZCS1988   | 0.75 - 1.00 | 19-25   | Single        | 16             | 405   | 20             | 510   | 4,480              | 2,030 |
| ZCS1989   | 1.00 - 1.50 | 25-38   | Single        | 18             | 455   | 24             | 610   | 6,272              | 2,845 |
| ZCS1990   | 1.50 - 2.00 | 38-50   | Double        | 21             | 535   | 29             | 735   | 8,960              | 4,065 |
| ZCS1991   | 2.00 - 2.50 | 50-63   | Double        | 24             | 610   | 34             | 865   | 8,960              | 4,065 |
| ZCS1992   | 2.50 - 3.50 | 63-89   | Double        | 27             | 685   | 39             | 990   | 10,752             | 4,875 |
| ZCS1993   | 3.50 - 4.50 | 89-115  | Double        | 27             | 685   | 39             | 990   | 12,544             | 5,690 |
| ZCS1994   | 4.50 - 5.50 | 115-140 | Double        | 27             | 685   | 39             | 990   | 12,544             | 5,690 |
| ZCS3994   | 5.50 - 7.00 | 140-180 | Double        | 24             | 610   | 39             | 990   | 4,500              | 2,009 |
| ZCS4069   | 8.0 - 9.0   | 203-229 | Double        | 59             | 1,500 | 74             | 1,880 | 20,000             | 8,928 |