



Legend™ 2-Part Labelling System – Laser Labels

With the Silver Fox 2-part labelling system you can make changes in seconds with no need to cut and re-terminate the wire. Simply remove the label from the tubing and pull through a new label.

A really easy and fast way of producing wire markers using a standard office laser printer.

Tubing is available in various sizes depending on the diameter of the cable, whatever the size, it still takes the same label. Additionally, the tubing and matching labels are available in three sizes; 20mm, 30mm and 50mm. The longer the label, the more characters that can be printed.

TESTING




| Test | Method |
|-----------------------------------|--|
| Moisture Resistance | MIL-STD-202G Method 106G |
| Low Temperature 72 hours @ -40°C | MIL-STD-810F Method 502.4 |
| High Temperature 500 hours @ 70°C | MIL-STD-202G Method 108A |
| Hydrogen Sulphide | H2S Sour Gas Exposure (2% H2S) |
| UV Weathering 500 hours* | ISO 4982 Part 3 Method A Cycle 1 |
| Salt Mist Spray | IEC60068-2-52 Test Kb Salt Mist (Cyclic) |

* Limited external applications generally away from direct sunlight but may be suitable in control boxes etc. Labels generally for internal use such as, control rooms, power stations, substations etc.

TECHNICAL DATA

| | |
|------------------|----------------|
| Printing method: | Standard Laser |
| Material: | Polyester |
| Colours: | White |
| Sheet Size: | A4 |
| RoHS: | Yes |
| Reach: | Yes |

HOW IT WORKS

| STEP 1 | STEP 2 | STEP 3 |
|---|--|---|
|  |  |  |
| Slide the tubing onto the cable/wire | Pull the printed label through the tubing | Tear/cut off tail |



Legend™ 2-Part Labelling System – Laser Labels

Additional Information

- Easy to use and apply
- Use with thermal or laser 2-part labelling system labels
- Choice of 3 lengths; 20mm, 30mm, 50mm
- Wide range of diameters from OD Ø 1.2mm to 14mm
- Because of this special design it is possible to slide the blank tubing onto the wire prior to termination. The label can then be inserted at any time during or after termination.

ORDER INFORMATION

| Product Code | Label Dims (mm) | Labels Per Sheet | Sheets per Pack | Labels per pack | Colour |
|--------------|-----------------|------------------|-----------------|-----------------|--------|
| L75/20L | 20 x 5 | 75 | 10/100 | 75 / 750 | ○ |
| L45/30L | 30 x 5 | 45 | 10/100 | 45 / 450 | ○ |
| L38/40L | 40 x 5 | 38 | 10/100 | 38 / 380 | ○ |



STORAGE INSTRUCTIONS

| | |
|----------------------|---|
| Storage Instructions | Store between 50°F (10°C) and 77°F (25°C) |
| Conditions | Keep in dark conditions |
| Humidity Resistance | 35% to 65% RH |

Disclaimer: The information contained in this datasheet is based on data we believe to be reliable and is given for information only and without guarantee and does not constitute a warranty. We are not able to anticipate every set of conditions, so always suggest that users should also satisfy themselves as to the suitability of our products for their particular environment and application and not make any assumptions based on information in this data sheet that is included or omitted. This datasheet supersedes any previous information/datasheet released and is subject to change without notice.