ISSUE 1 - FEB 2017

PRODUCT INFORMATION

Ridgiduct Motorway Communications come in sizes 94, 100 and 150mm as a sealed system specifically designed for motorway communications applications.



Applications

For motorway communications. For Scotland, print is available for motorway comms/power.

Performance

Ridgiduct is manufactured from high density Polyethylene (HDPE) and is supplied with a black Polypropylene (PP) coupler. The internal wall has a static coefficient of less than 0.22. Ridgiduct also has adequate resistance to attack from chemicals likely to occur in soils and ground water.

Key benefits

- IP67 Rated Sealed System when installed with CRD Coupling and SRD Sealing Ring
- BBA HAPAS certified as a fully sealed system
- Complies with BS EN 61386-24:2010, Type 450N, normal duty impact resistance
- Network Rail PADS approved
- Print options available
- Can be used for trenchless applications
- · Low weight, flexible, durable and high strength
- Good impact resistance even at lower temperatures
- Comtite[™] Ducting Plug available to ensure full compliance with Series 1500 specification for Highway Works (MCHW)





RIDGIDUCT MOTORWAY COMMUNICATIONS DUCT							
ID (mm)	OD (mm)	LENGTH (m)	CODE	PACK QTY			
94	110	6	RB94X6PMCPPE/1	95			
100	118	6	RB100X6PMCPPE	85			
150	178	6	RB150X6PMCPPE ▲	36			

▲ Made to order and subject to lead times.

Conforms to Highways Agency Specification for sealed systems.

For Scottish market printed Motorway Comms/Power.

Other print options available.

JOINTING						
ID (mm)	COUPLING CODE	SEAL CODE				
94	CRD94	SRD94/1				
100	CRD100	SRD100				
150	CRD150	SRD150				

1 coupler and 2 seals per joint.

RIDGIDUCT LONG RADIUS DRAWN BENDS							
ID mm	BEND RADIUS mm	ANGLE	COUPLER CODES	PACK QTY			
94mm	420	11.25°	RBDB94X11X0.42	10			
	420	22.5°	RBDB94X22X0.42	10			
	420	45°	RBDB94X45X0.42	7			
	420	90°	RBDB94X90X0.42	7			
100mm	420	11.25°	RBDB100X11X0.42	10			
	420	22.5°	RBDB100X22X0.42	10			
	420	45°	RBDB100X45X0.42	7			
	420	90°	RBDB100X90X0.42	7			
	610	11.25°	RBDB150X11X0.61	5			
150mm	610	22.5°	RBDB150X22X0.61	5			
	610	45°	RBDB150X45X0.61	4			
	610	90°	RBDB150X90X0.61	3			

Note: Bends are supplied in the colour black only.

All descriptions and illustrations in this publication are intended for guidance only and shall not constitute a 'sale by description'. All dimensions given are nominal and Polypipe may modify and change the information, products and specifications from time to time for a variety of reasons, without prior notice. The information in this publication is provided 'as is' on February 2017. Updates will not be issued automatically. This information is not intended to have any legal effect, whether by way of advice, representation or warranty (express or implied). We accept no liability whatsoever (to the extent permitted by law) if you place any reliance on this publication you must do so at your own risk. All rights reserved. Copyright in this publication belongs to Polypipe and all such copyright may not be used, sold, copied or reproduced in whole or part in any manner in any media to any person without prior consent. Polypipe is a registered trademark of Polypipe. All Polypipe products are protected by Design Right under CDPA 1988. Copyright © 2017 Polypipe. All rights reserved.



