



**Standards** EN 60903:2003 / IEC 60903:2014 IEC 61482-2 ASTM F2675

Network Type: MV

## SICAME GROUP

**CGM-2..** 

Mechanical and Arc Flash insulating gloves, class 2, length: 360 mm

## **Application:**

- · Wellfit finish: soft, supple, durable and ergonomic with high flexibility to ease the
- Convenient to any hand shape.
- Protection against thermal hazards from an electric arc 12 cal/cm<sup>2</sup> as a standard. APC 2 (box test 7 kA).
- Resistant: latex with reinforced mechanical protection against tearing. To be used without over-gloves.

## Features:

- Electrical insulating gloves, class 2 (17 000 V AC, 25 500 V DC). Protection against electric arc.
- Cut edges.
- · Material: bicolor natural latex. (exterior: orange, interior: natural).
- Traceability through flashcode on color-coded label. The color is according to the class.
- Category: RC (Acid, Ozone, Cold, Oil resistance).







Ref.	Functionality	Protection	Arc	Operating Voltage	
	Size	Electrical Protection Class	ATPV Arc Rating	AC	DC
CGM-2-08	8	2	12	17 000 V	25 500 V
CGM-2-09	9	2	12	17 000 V	25 500 V
CGM-2-10	10	2	12	17 000 V	25 500 V
CGM-2-11	11	2	12	17 000 V	25 500 V
CGM-2-12	12	2	12	17 000 V	25 500 V

