



Arc Flash equipment

"Arc flash" face shield kit (12 cal/cm²)

Reference	KIT-ARC-01	kg
Composition		1.5
MO-187	1 Face shield with chin cup 12 cal/cm ² , absorbs > 99.9% of harmful UV radiation, 70% light transmission, tested to ASTM F 2178 specifications	
MO-182/1-B	1 ABS helmet electrically insulated EN397, EN 50365, ANSI Z89.1 20kV.	
M-87413	1 carrying bag for face shield and helmet	



NFPA 70E

CE



"Arc flash" Helmet (20 cal/cm²)

The only one all integrated helmet with "arc flash" faceshield on the market.

Reference	Characteristics	kg
MO-180-ARC	Integrated helmet with "arc flash" Faceshield	1.2

Retractable Faceshield high visibility & UV Protection. According to NFPA 70E ASTM F 2178 IEC 61482-2 IEC 61482-1-1 IEC 61482-1-2 class 2 GS-ET 29

Mechanical & Electrical Protection helmet EN 397 EN 50365

Light, compact and flexible protection in Arc rated fabric ASTM F1959 ASTM F1506



"Arc flash" coverall double zipper

Protects against the thermal hazards of an electric arc. Easy to put on.

Reference	Characteristics	kg
MV-105(*)	Ultra soft	1.4

(*) to complete by size M, L ou XL. Other sizes on request.

Double zipper along the entire length.



NFPA 70E



IEC 61482-2

CE



Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com

↔ Total length

📦 Packaging

⚖ Weight