

TABLE OF CHARACTERISTICS

	Voltage	Frequency	Threshold	Polarity DC	ϕ Indication	Continuity R	Continuity Tempo	Digital screen	Phase rotation	Lighting unit
MS-917-L	± 12 to 690 Vac / 750 Vdc	50 - 60 Hz	7 thresholds	✓	✓	200 Ω	✗	✗	✗	✗
MS-918-L	900 Vac / 1000 Vdc	50 - 60 and 400 Hz	8 thresholds	✓	✓	80 Ω	10s	✗	✓	✓
MS-920-EX	690 Vac / 800 Vdc	50 - 60 Hz	Resolution 1 V	✓	✓	100 Ω	10s	✓	✓	✓

Distributed by :



**THORNE &
DERRICK
INTERNATIONAL**



Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com

SICAME GROUP

09/2015

Detex™ +

.....MS-917 / MS-918 / MS-920

**VOLTAGE
DETECTOR**



SICAME GROUP

Detex™ +

..... MS-917 / MS-918 / MS-920

IEC 61243-3



**EASY TO USE,
ROBUST
AND ERGONOMIC,
OUR VERSATILE
DEVICES ARE
YOUR BEST
SAFETY
ASSISTANTS!**

Detex™ +
..... RANGE

ensures both voltage detector function in full compliance with **EN 50-110** and essential functions to your normal operations, such as continuity, rotating field and phase indication.



**DC VOLTAGES
UP TO 1000Vdc**

**AC VOLTAGES
UP TO 900Vac**
A wider voltage range for all your LV operations

Polarity
Phase rotation indicator is more user friendly

Phase indication

Self-test



Ø 2 mm probes

**UP TO
1000 Vdc
900 Vac**

**IP65
CATEGORY
IV
600 V**

**Ω
A LOW
CONTINUITY
RESISTANCE
VALUE**

**ROBUST AND
ERGONOMIC**

With a high degree of sealing (IP65) and good impact resistance (IK06) our range is suitable for all environments.

**SUITABLE
FOR SAFETY
PLUGS**

For 2P+T 10/16A with 19mm spacing.

**LIGHTING
LAMP**



**SELF-
TEST**

Allows the complete check up of the voltage detector (batteries, leads, electronic).

**DIGITAL
DISPLAY**

MS-920 serie only.



**AT HOME
ANYWHERE**

With its board hanger MS-920 serie only.

