



FILoSeal+HD FIRE

Re-enterable Duct Sealing System

FILoSeal+HD FIRE



FILoSeal+HD FIRE



FILoSeal+HD FIRE



FILoSeal+HD FIRE



- Up to 4 hours fire resistance in transit frames (single side)
- Up to 4 hours fire resistance in ducts
- Tested to BS EN1366-3 2009
- Upto 2 bar Pressure Resistance
- 100Kg pulling Force on the cables when sealed
- 10xd at 45°, with 1 bar pressure bending test

Duct sealing system FiloSeal+HD FIRE is our new highly certified fire, gas and water sealing system for both ducts and transit frames

FiloSeal+HD FIRE provides a strong support system using our specially formulated material called Formite which builds up like a honeycomb structure.

FiloSeal+HD FIRE is suitable for sealing any cable configuration or pipes contained in one duct and also allows easy re-entry of the seal to add or remove cables or pipes as required.

The Filoform duct sealing system FiloSeal+HD FIRE uses our MD+ sealant which is easily applied from a skeleton gun. The high quality, one component, flexible sealant "MD+" is based on a silicon compound that cures with air (Humidity).

The unique design of the hexagonal tubes makes positioning and separation of the cables very simple while also providing a strong backing for the MD+ to be applied on.

- High levels of Gas and Water tightness
- Excellent adhesion, applicable to all common building materials
- Shows fire resistance properties
- Resistant against Water, Alkaline, Chemical agents
- Resistant to Hydrogen Sulphide / Methane and many other Gases (NedLab)
- Non corrosive
- Solvent free
- Shock absorbing
- Non toxic, neutral and almost odourless
- Complies with ATEX regulations
- Suitable for any shaped duct / bore hole / opening
- Quick and easy installation
- A complete kit
- Seals all know materials, PVC & PE sheathed cables, PILC, (HD) PE pipes
- Suitable for renovations, can be installed retrospectively
- Resistant to Rats
- Resistant to termites (Mastotermes Darwiniensis) Northern Australian termites

FILoSeal+HD FIRE



FILoSeal+HD FIRE



FILoSeal+HD FIRE



Part number and kit details below:

Item number	Description	Maximum duct diameter (mm)
280070	FiloSeal+HD FIRE 75 > 110mm	110mm
280080	FiloSeal+HD FIRE 125 > 160mm	160mm
280070	FiloSeal+HD FIRE 180mm	180mm
280080	FiloSeal+HD FIRE 200mm	200mm
280070	FiloSeal+HD FIRE 225mm	225mm
280080	FiloSeal+HD FIRE 250mm	250mm



**THORNE &
DERRICK**
INTERNATIONAL

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com