

## COPPER TUBE LUGS 4-ESI FIXING A-4ESI



THORNE &  
DERRICK  
INTERNATIONAL

Thorne & Derrick  
+44 (0) 191 410 4292  
www.powerandcables.com

A-4ESI series lugs are made from high purity electrolytic copper tube, annealed and tin plated. The four hole stud fixing in accordance with E.A. specifications ensures compatibility with most transformer fixing arrangements.



### Technical characteristics


Material (Body)

Tinned electrolytic copper electrolytically

Material (Fixing)

Tinned electrolytic copper electrolytically

### Media gallery



### List of products

➤ **A-4ESI** Cable type: copper, Maximum section: 185 mm<sup>2</sup>



Type	B	L	Number the hole	Pack qty	Min. pack qty	M	N	Center distances	Øi
A37-4ESI	61 mm	124 mm	4	20	10	20 mm	15 mm	25L-35B	19.2 mm

➤ **A-4ESI** Cable type: flexible copper, Maximum section: 185 mm<sup>2</sup>





Type	B	L	Number the hole	Pack qty	Min. pack qty	M	N	Center distances	Øi
A37-4ESI	61 mm	124 mm	4	20	10	20 mm	15 mm	25L-35B	19.2 mm

**> A-4ESI** Cable type: copper, Maximum section: 240 mm<sup>2</sup>



Type	B	L	Number the hole	Pack qty	Min. pack qty	M	N	Center distances	Øi
A48-4ESI	61 mm	128 mm	4	20	10	20 mm	15 mm	25L-35B	21.1 mm

**> A-4ESI** Cable type: flexible copper, Maximum section: 240 mm<sup>2</sup>



Type	B	L	Number the hole	Pack qty	Min. pack qty	M	N	Center distances	Øi
A48-4ESI	61 mm	128 mm	4	20	10	20 mm	15 mm	25L-35B	21.1 mm

**> A-4ESI** Cable type: flexible copper, Maximum section: 300 mm<sup>2</sup>



Type	B	L	Number the hole	Pack qty	Min. pack qty	M	N	Center distances	Øi
A60-4ESI	61 mm	133 mm	4	15	5	20 mm	15 mm	25L-35B	23.7 mm

**> A-4ESI** Cable type: copper, Maximum section: 300 mm<sup>2</sup>



Type	B	L	Number the hole	Pack qty	Min. pack qty	M	N	Center distances	Øi
A60-4ESI	61 mm	133 mm	4	15	5	20 mm	15 mm	25L-35B	23.7 mm

**> A-4ESI** Cable type: flexible copper, Maximum section: 400 mm<sup>2</sup>



Type	B	L	Number the hole	Pack qty	Min. pack qty	M	N	Center distances	Øi
A80-4ESI	61 mm	134 mm	4	15	5	20 mm	15 mm	25L-35B	27 mm

**> A-4ESI** Cable type: copper, Maximum section: 400 mm<sup>2</sup>



Type	B	L	Number the hole	Pack qty	Min. pack qty	M	N	Center distances	Øi
A80-4ESI	61 mm	134 mm	4	15	5	20 mm	15 mm	25L-35B	27 mm

**A-4ESI** Cable type: flexible copper, Maximum section: 500 mm<sup>2</sup>



Type	B	L	Number the hole	Pack qty	Min. pack qty	M	N	Center distances	Øi
A100-4ESI	61 mm	139 mm	4	10	5	20 mm	15 mm	25L-35B	30.3 mm

**A-4ESI** Cable type: copper, Maximum section: 500 mm<sup>2</sup>



Type	B	L	Number the hole	Pack qty	Min. pack qty	M	N	Center distances	Øi
A100-4ESI	61 mm	139 mm	4	10	5	20 mm	15 mm	25L-35B	30.3 mm

**A-4ESI** Cable type: flexible copper, Maximum section: 630 mm<sup>2</sup>



Type	B	L	Number the hole	Pack qty	Min. pack qty	M	N	Center distances	Øi
A120-4ESI	61 mm	144 mm	4	10	5	20 mm	15 mm	25L-35B	33.4 mm

**A-4ESI** Cable type: copper, Maximum section: 630 mm<sup>2</sup>



Type	B	L	Number the hole	Pack qty	Min. pack qty	M	N	Center distances	Øi
A120-4ESI	61 mm	144 mm	4	10	5	20 mm	15 mm	25L-35B	33.4 mm

**A-4ESI** Cable type: flexible copper, Maximum section: 800 mm<sup>2</sup>



Type	B	L	Number the hole	Pack qty	Min. pack qty	M	N	Center distances	Øi
A160-4ESI	61 mm	158 mm	4	8	1	20 mm	15 mm	25L-35B	38 mm

**A-4ESI** Cable type: copper, Maximum section: 800 mm<sup>2</sup>



Type	B	L	Number the hole	Pack qty	Min. pack qty	M	N	Center distances	Øi
A160-4ESI	61 mm	158 mm	4	8	1	20 mm	15 mm	25L-35B	38 mm



THORNE &  
**DERRICK**  
INTERNATIONAL

**Thorne & Derrick**  
+44 (0) 191 410 4292  
[www.powerandcables.com](http://www.powerandcables.com)