

MV cables Tools

CWB/18-60



Section

MV Semi-conductor

Application

Field
Laboratory



PRODUCT BENEFITS

No silicon needed
Fine tuning of the blade with a 'click' for each 1/10 mm
Very smooth finish over the insulation
Adjustable length of semiconductor cutback : 25-30-40 mm / 0,984-1,181-1,575 in

TOOL CAPACITY

| | |
|---|---------------------------------------|
| Diameter | 18 - 60 mm 0,709 - 2,362 inch |
| Thickness capacity | 1,1 mm / 0,043 in |
| Angle of the chamfer on the semiconductor | 8° |
| Remaining length of the semiconductor | 25-30-40 mm / 0,984-1,181-1,575 in |

TOOL DIMENSIONS

| | |
|--------------------|---------|
| Length | 235 mm |
| Width | 125 mm |
| Height | 90 mm |
| Weight without box | 0,85 Kg |
| Packaging | None |

Tool to remove bonded semiconductor with chamfer on the semiconductor cutback

TO DO WHAT

The CWB/18-60 enables the user to easily remove the bonded semi-conductor with a chamfer on the transition, leaving a very smooth finish over the insulation
The CWB 18-60 works without silicone



Options

SGM - Large size pouch

Spare part

LCWB-SP2 - Spare blade for bonded semiconductor with chamfer 8°

Associated tool

LCWB-FEP - Spare blade for bonded semiconductor with chamfer 13°
GRI-RTE - Scraper for residues of bonded semiconductor screen with protection pouch
PG3HTA/2530 - Pliers for MV cables outer sheath
BRMRD1E - Tool to remove insulation



**THORNE &
DERRICK
INTERNATIONAL**

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com

MV cables Tools

CWB/18-60



| Part Number | Diameter | Tool capacity | | | Dimensions | | | Packaging |
|----------------------|--------------------------------|--------------------|---|---------------------------------------|--------------------|--------------------|-------------------|-----------|
| | | Thickness capacity | Angle of the chamfer on the semiconductor | Remaining length of the semiconductor | Length | Width | Height | |
| CWB/18-60 | 18 - 60 mm 0,709 - 2,362 in | 1,1 mm / 0,043 in | 8° | 25-30-40 mm / 0,984-1,181-1,575 in | 235 mm 9,252 in | 125 mm 4,921 in | 90 mm 3,543 in | none |
| CWB/18-60-FEP | 18 - 60 mm 0,709 - 2,362 in | 1,8 mm / 0,071 in | 13° | 25-30-40 mm / 0,984-1,181-1,575 in | 235 mm 9,252 in | 125 mm 4,921 in | 90 mm 3,543 in | none |



**THORNE &
DERRICK
INTERNATIONAL**

Thorne & Derrick

+44 (0) 191 410 4292

www.powerandcables.com