

MV cables Tools

CWF3/60



Section

MV Multifunction

Application

Field
Laboratory



PRODUCT BENEFITS

Tuning of the pitch of the tool (width of the chip sheath)
Embedded wear pads to protect the tool from the contact with the outer sheath
All in one

TOOL CAPACITY

| | |
|---|---------------------------------------|
| Diameter | 16 - 58 mm 0,630 - 2,283 inch |
| Peelable semiconductor thickness capacity | Option |
| Insulation thickness capacity | 7 mm / 0,276 in |
| Remaining length of the semiconductor | 30-40-45 mm / 1,181-1,575-1,772 in |

TOOL DIMENSIONS

| | |
|--------------------|---------|
| Length | 305 mm |
| Width | 115 mm |
| Height | 165 mm |
| Weight without box | 1,67 Kg |
| Packaging | None |

Multi-function tool for outer sheath and insulation

TO DO WHAT

The CWF3/60 tools enables the user to :
Remove the outer sheath (PE-PVC-PR) with a straight and neat cut
Set the length and remove the insulation with a straight and neat cut
Other functions in option



Options

SRC-W - Scoring stylus for peelable semiconductor with chamfer on the transition
SCH-D - Cutting pencil to chamfer the end of the insulation
SFC-D07 - Scoring pencil with fixed depth 0,7mm for peelable semiconductor with chamfer
SR-W - Scoring stylus for peelable semiconductor

Spare part

KIT-MF3/40 - Protective wear pads
LCWF2 - Spare blade for outer sheath and insulation CWF3/60
BR - Thrust to set the length of insulation to be remove
VBB1 - Screw for locking the thrust
PCR - Quick set up right angled 45° handle
196855 - Straight handle M10
108098 - Clamping knob for blade

Associated tool

DSP - Peelable semiconductor lifter
C-SR - Wrench to replace the semiconductor blade



**THORNE &
DERRICK
INTERNATIONAL**

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com

MV cables Tools
CWF3/60



| Part Number | Diameter | Tool capacity | | | Dimensions | | | Packaging |
|-------------|--------------------------------|---|-------------------------------|---------------------------------------|---------------------|--------------------|--------------------|-----------|
| | | Peable semiconductor thickness capacity | Insulation thickness capacity | Remaining length of the semiconductor | Length | Width | Height | |
| CWF3/60 | 16 - 58 mm 0,630 - 2,283 in | Option | 7 mm / 0,276 in | 30-40-45 mm / 1,181-1,575-1,772 in | 305 mm 12,008 in | 115 mm 4,528 in | 165 mm 6,496 in | none |



THORNE &
DERRICK
 INTERNATIONAL

Thorne & Derrick
 +44 (0) 191 410 4292
www.powerandcables.com