

## Section

HV Outer sheath

## Application

Field

Laboratory



## PRODUCT BENEFITS

Sound alert when the blade is touching the aluminium/lead shield

## TOOL CAPACITY

**Diameter** 50 - 95 mm  
1,969 - 3,740 inch

**Thickness capacity** 7 mm / 0,276 in

**Shield detection** Yes

## TOOL DIMENSIONS

**Length** 260 mm

**Width** 160 mm

**Height** 320 mm

**Weight without box** 4,1 Kg

**Packaging** Case

## Stripping tool for HV and EHV cable's outer sheath and shield

### TO DO WHAT

The DMS 50-95 enables the user to remove the outer sheath and the aluminium/lead shield on HV and EHV cable by successively performing a longitudinal and circular cut



### Spare part

LDMS - Spare blade for outer sheath and shield  
193725 - 6 volts battery diameter 13x25 mm

### Associated tool

EGA - HV and EHV cable's outer sheath and shield spreaders

BMFD/55-160 - Thrust to stop the tool

EV-HTB - HV and EHV cable's outer sheath and shield splitters

EVP - HV and EHV cable's lead sheath splitters



**THORNE &  
DERRICK  
INTERNATIONAL**

**Thorne & Derrick**  
+44 (0) 191 410 4292  
[www.powerandcables.com](http://www.powerandcables.com)

HV cables Tools

# DMS 50-95



| Part Number | Diameter                        | Tool capacity      |                  | Dimensions          |                    |                     | Packaging |
|-------------|---------------------------------|--------------------|------------------|---------------------|--------------------|---------------------|-----------|
|             |                                 | Thickness capacity | Shield detection | Length              | Width              | Height              |           |
| DM 50-95    | 50 - 95 mm<br>1,969 - 3,740 in  | 7 mm / 0,276 in    | No               | 260 mm<br>10,236 in | 160 mm<br>6,299 in | 320 mm<br>12,598 in | case      |
| DM 95-145   | 95 - 145 mm<br>3,740 - 5,709 in | 11 mm / 0,433 in   | No               | 280 mm<br>11,024 in | 180 mm<br>7,087 in | 360 mm<br>14,173 in | case      |
| DMS 50-95   | 50 - 95 mm<br>1,969 - 3,740 in  | 7 mm / 0,276 in    | Yes              | 260 mm<br>10,236 in | 160 mm<br>6,299 in | 320 mm<br>12,598 in | case      |
| DMS 95-145  | 95 - 145 mm<br>3,740 - 5,709 in | 11 mm / 0,433 in   | Yes              | 280 mm<br>11,024 in | 180 mm<br>7,087 in | 360 mm<br>14,173 in | case      |



THORNE &  
**DERRICK**  
INTERNATIONAL

Thorne & Derrick  
+44 (0) 191 410 4292  
[www.powerandcables.com](http://www.powerandcables.com)