

**Section**

MV Insulation

**Application**Field  
Laboratory**PRODUCT BENEFITS**

No setting needed

**TOOL CAPACITY**

|                 |                                  |
|-----------------|----------------------------------|
| <b>Diameter</b> | 14 - 40 mm<br>0,551 - 1,575 inch |
|-----------------|----------------------------------|

**TOOL DIMENSIONS**

|                    |         |
|--------------------|---------|
| Length             | 275 mm  |
| Width              | 75 mm   |
| Height             | 45 mm   |
| Weight without box | 0,56 Kg |
| Packaging          | None    |

## Tool to chamfer insulation

**TO DO WHAT**

The LHA enables the user to realise a chamfer of 30° at the extremity of the insulation of MV cables

**Spare part**

LHAC - Spare blade chamfer insulation

**Associated tool**

BRMRD1E - Tool to remove insulation

ROTO-TMG - Connector holder for bolted and clamping connections

122818 - Allen key size 3mm



**THORNE &  
DERRICK  
INTERNATIONAL**

**Thorne & Derrick**

+44 (0) 191 410 4292

[www.powerandcables.com](http://www.powerandcables.com)



| Part Number | Diameter                       | Tool capacity | Dimensions          |                    |                   | Packaging |
|-------------|--------------------------------|---------------|---------------------|--------------------|-------------------|-----------|
|             |                                |               | Length              | Width              | Height            |           |
| LHA         | 14 - 40 mm<br>0,551 - 1,575 in |               | 275 mm<br>10,827 in | 75 mm<br>2,953 in  | 45 mm<br>1,772 in | none      |
| LHA/ 60     | 20 - 55 mm<br>0,787 - 2,165 in |               | 265 mm<br>10,433 in | 105 mm<br>4,134 in | 45 mm<br>1,772 in | none      |
| LHA2        | 38 - 60 mm<br>1,496 - 2,362 in |               | 280 mm<br>11,024 in | 100 mm<br>3,937 in | 45 mm<br>1,772 in | none      |

