

MV cables Tools

LHS2



Section

MV Semi-conductor

Application

Field



PRODUCT BENEFITS

Back-iron to set the pitch of the tool in order to get a good result over the insulation

TOOL CAPACITY

Diameter 38 - 60 mm
1,496 - 2,362 inch

Max cutting depth 5 mm / 0,197 in

TOOL DIMENSIONS

Length 425 mm

Width 105 mm

Height 85 mm

Weight without box 2 Kg

Packaging None

Tool for bonded non peelable semiconductor with silicone

TO DO WHAT

The LHS2 enables the user to remove bonded semiconductor realizing a right stop. Using the tool with silicone



Spare part

LASC2 - Blade for non-peelable semiconductor

Associated tool

LH2 - Monofunction tool for insulation

PRG3/C20-L222830 - Pliers for MV cable outer sheath with 3 adjustable longitudinal cutting depth

BMF2 - Thrust to stop the tool



**THORNE &
DERRICK
INTERNATIONAL**

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com



| Part Number | D iameter | Tool capacity | D imensions | | | Packaging |
|-------------|----------------------------------|-------------------|---------------------|--------------------|--------------------|-----------|
| | | Max cutting depth | Length | Width | Height | |
| LHS2 | 38 - 60 mm 1,496 - 2,362 in | 5 mm / 0,197 in | 425 mm 16,732 in | 105 mm 4,134 in | 85 mm 3,346 in | none |
| LHS3 | 60 - 80 mm 2,362 - 3,150 in | 10 mm / 0,394 in | 460 mm 18,110 in | 130 mm 5,118 in | 85 mm 3,346 in | none |
| LHS4 | 80 - 110 mm 3,150 - 4,331 in | 12 mm / 0,473 in | 640 mm 25,197 in | 155 mm 6,102 in | 95 mm 3,740 in | none |
| LHS5 | 100 - 140 mm 3,937 - 5,512 in | 8 mm / 0,315 in | 730 mm 28,740 in | 195 mm 7,677 in | 115 mm 4,528 in | none |

