

HV cables Tools

LHS3



Section

HV Semi-conductor

Application

Field



PRODUCT BENEFITS

Back-iron to set the pitch of the tool in order to get a good result over the insulation

TOOL CAPACITY

Diameter 60 - 80 mm
2,362 - 3,150 inch

Max cutting depth 10 mm / 0,394 in

TOOL DIMENSIONS

Length	460 mm
Width	130 mm
Height	85 mm
Weight without box	3 Kg
Packaging	None

Tool for bonded non peelable semiconductor with silicone

TO DO WHAT

The LHS3 enables the user to remove bonded semiconductor realizing a right stop. Using the tool with silicone



Spare part

LASC3 - Blade for non-peelable semiconductor

Associated tool

LH3 - Monofunction tool for insulation

PRG4/C30-L283335 - Pliers for MV cable outer sheath with 3 adjustable longitudinal cutting depth

BMF2 - Thrust to stop the tool



THORNE &
DERRICK
INTERNATIONAL

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com

HV cables Tools

LHS3



Part Number	D iameter	Tool capacity	D imensions			Packaging
		Max cutting depth	Length	Width	Height	
LHS2	38 - 60 mm 1,496 - 2,362 in	5 mm / 0,197 in	425 mm 16,732 in	105 mm 4,134 in	85 mm 3,346 in	none
LHS3	60 - 80 mm 2,362 - 3,150 in	10 mm / 0,394 in	460 mm 18,110 in	130 mm 5,118 in	85 mm 3,346 in	none
LHS4	80 - 110 mm 3,150 - 4,331 in	12 mm / 0,473 in	640 mm 25,197 in	155 mm 6,102 in	95 mm 3,740 in	none
LHS5	100 - 140 mm 3,937 - 5,512 in	8 mm / 0,315 in	730 mm 28,740 in	195 mm 7,677 in	115 mm 4,528 in	none



THORNE &
DERRICK
INTERNATIONAL

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com