

Certifications

Approved by ERDF

Section

MV Multifunction

Application

Field
Laboratory



PRODUCT BENEFITS

Tuning of the pitch of the tool
Embedded wear pads to protect the tool from the contact with the outer sheath

TOOL CAPACITY

Diameter	16 - 40 mm 0,630 - 1,575 inch
----------	----------------------------------

Outer sheath and insulation thickness capacity	7 mm / 0,275 mm
--	-----------------

TOOL DIMENSIONS

Length	150 mm
Width	80 mm
Height	100 mm
Weight without box	1,24 Kg
Packaging	None

Multifunction tool for outer sheath and insulation

TO DO WHAT

The MF2/40 enables the user to :
Remove the outer sheath (PE-PVC-PR) with a straight and neat cut
Set the length and remove thicker insulation with a straight and neat cut

Spare part

KIT-MF3/40 - Protective wear pads
LMF2 - Spare blade for primary insulation
BR - Thrust to set the length of insulation to be remove
VBB1 - Screw for locking the thrust
PCR - Quick set up right angled 45° handle
196855 - Straight handle M10
108098 - Clamping knob for blade

Associated tool

MF1+/25 - Multifunction tool for bonded semiconductor
SRC - Scoring stylus for peelable semiconductor with chamfer



THORNE &
DERRICK
INTERNATIONAL

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com

MV cables Tools

MF2/40

Part Number	Diameter	Tool capacity	Dimensions			Packaging
		O uter sheath and insulation thickness capacity	Length	Width	H eight	
MF2/40	16 - 40 mm 0,630 - 1,575 in	7 mm / 0,275 mm	150 mm 5,906 in	80 mm 3,150 in	100 mm 3,937 in	none
MF2/40-S	16 - 40 mm 0,630 - 1,575 in	11 mm / 0,433 in	150 mm 5,906 in	80 mm 3,150 in	100 mm 3,937 in	none
MF2/60	16 - 58 mm 0,630 - 2,283 in	7 mm / 0,275 mm	170 mm 6,693 in	90 mm 3,543 in	120 mm 4,724 in	none
MF2/60-S	16 - 58 mm 0,630 - 2,283 in	11 mm / 0,433 in	170 mm 6,693 in	90 mm 3,543 in	120 mm 4,724 in	none



THORNE &
DERRICK
INTERNATIONAL

Thorne & Derrick

+44 (0) 191 410 4292

www.powerandcables.com