



**Certifications**

Approved by ERDF

**Section**

MV Multifunction

**Application**

Field  
Laboratory



**PRODUCT BENEFITS**

Tuning of the pitch of the tool  
Embedded wear pads to protect the tool from the contact with the outer sheath

**TOOL CAPACITY**

<b>Diameter</b>	16 - 58 mm 0,630 - 2,283 inch
<b>Peelable semi conductor thickness capacity</b>	0.4 - 1.5 mm
<b>Insulation thickness capacity</b>	7 mm
<b>Stylus Included</b>	SR

**TOOL DIMENSIONS**

<b>Length</b>	305 mm
<b>Width</b>	115 mm
<b>Height</b>	165 mm
<b>Weight without box</b>	1,75 Kg
<b>Packaging</b>	None

## Multifunction tool for outer sheath, peelable semiconductor and insulation

**TO DO WHAT**

The MF3/60 tools enables the user to :  
Remove the outer sheath (PE-PVC-PR) with a straight and neat cut  
Score the peelable semiconductor (with the SR scoring stylus delivered with the tool)  
Set the length to be removed and remove the insulation with a straight and neat cut



**Options**

SRC - Scoring stylus for peelable semiconductor with chamfer  
SCH - Chamfering stylus for insulation

**Spare part**

- KIT-MF3/40 - Protective wear pads
- SR - Scoring stylus for peelable semiconductor
- LS - Spare blade for peelable semiconductor
- LMF2 - Spare blade for primary insulation
- BR - Thrust to set the length of insulation to be remove
- VBB1 - Screw for locking the thrust
- PCR - Quick set up right angled 45° handle
- 196855 - Straight handle M10
- 108098 - Clamping knob for blade

**Associated tool**

- ALROC-FENTE - Tool to perform slits on cable's outer sheath
- ROTO-TMG - Connector holder for bolted and clamping connections
- DSP - Peelable semiconductor lifter





Part Number	Diameter	Tool capacity			Dimensions			Packaging
		Peelable semi conductor thickness capacity	Insulation thickness capacity	Stylus Included	Length	Width	Height	
MF3/40	16 - 40 mm 0,630 - 1,575 in	0.4 - 1.5 mm	7 mm	SR	305 mm 12,008 in	100 mm 3,937 in	165 mm 6,496 in	none
MF3/40-C	16 - 40 mm 0,630 - 1,575 in	0.4 - 1.5 mm	7 mm	SRC	305 mm 12,008 in	100 mm 3,937 in	165 mm 6,496 in	none
MF3/40-SR	16 - 40 mm 0,630 - 1,575 in	0.4 - 1.5 mm	11 mm	SR	305 mm 12,008 in	100 mm 3,937 in	165 mm 6,496 in	none
MF3/40-SRC	16 - 40 mm 0,630 - 1,575 in	0.4 - 1.5 mm	11 mm	SRC	305 mm 12,008 in	100 mm 3,937 in	165 mm 6,496 in	none
MF3/40-SSR	16 - 40 mm 0,630 - 1,575 in	Option	7 mm	None	305 mm 12,008 in	100 mm 3,937 in	165 mm 6,496 in	none
MF3/60	16 - 58 mm 0,630 - 2,283 in	0.4 - 1.5 mm	7 mm	SR	305 mm 12,008 in	115 mm 4,528 in	165 mm 6,496 in	none
MF3/60-C	16 - 58 mm 0,630 - 2,283 in	0.4 - 1.5 mm	7 mm	SRC	305 mm 12,008 in	115 mm 4,528 in	165 mm 6,496 in	none
MF3/60-SR	16 - 58 mm 0,630 - 2,283 in	0.4 - 1.5 mm	11 mm	SR	305 mm 12,008 in	115 mm 4,528 in	165 mm 6,496 in	none
MF3/60-SRC	16 - 58 mm 0,630 - 2,283 in	0.4 - 1.5 mm	11 mm	SRC	305 mm 12,008 in	115 mm 4,528 in	165 mm 6,496 in	none
MF3/60-SSR	16 - 58 mm 0,630 - 2,283 in	Option	7 mm	None	305 mm 12,008 in	115 mm 4,528 in	165 mm 6,496 in	none

