

Certifications

Approved by ERDF

Section

MV Multifunction

ApplicationField
Laboratory**PRODUCT BENEFITS**

Tuning of the pitch of the tool
Embedded wear pads to protect the tool from the contact with the outer sheath

TOOL CAPACITY

Diameter	16 - 58 mm 0,630 - 2,283 inch
Peelable semicon thickness capacity	Option
Insulation thickness capacity	7 mm
Stylus included	None

TOOL DIMENSIONS

Length	305 mm
Width	115 mm
Height	165 mm
Weight without box	1,67 Kg
Packaging	None

Multifunction tool for outer sheath and insulation without stylus

TO DO WHAT

The MF3/60-SSR tools enables the user to :
Remove the outer sheath (PE-PVC-PR) with a straight and neat cut
Set the length to be removed and remove the insulation with a straight and neat cut

**Options**

SR - Scoring stylus for peelable semiconductor
SRC - Scoring stylus for peelable semiconductor with chamfer
SCH - Chamfering stylus for insulation

Spare part

KIT-MF3/40 - Protective wear pads
LMF2 - Spare blade for primary insulation
BR - Thrust to set the length of insulation to be remove
VBB1 - S crew for locking the thrust
PCR - Quick set up right angled 45° handle
196855 - S traight handle M10
108098 - Clamping knob for blade

Associated tool

ALROC-FENTE - Tool to perform slits on cable's outer sheath
ROTO-TMG - Connector holder for bolted and clamping connections
DSP - Peelable semiconductor lifter



THORNE &
DERRICK
INTERNATIONAL

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com



Part Number	Diameter	Tool capacity			Dimensions			Packaging
		Pelable semicon thickness capacity	Insulation thickness capacity	Stylus included	Length	Width	Height	
MF3/40	16 - 40 mm 0,630 - 1,575 in	0.4 - 1.5 mm	7 mm	SR	305 mm 12,008 in	100 mm 3,937 in	165 mm 6,496 in	none
MF3/40-C	16 - 40 mm 0,630 - 1,575 in	0.4 - 1.5 mm	7 mm	SR C	305 mm 12,008 in	100 mm 3,937 in	165 mm 6,496 in	none
MF3/40-SR	16 - 40 mm 0,630 - 1,575 in	0.4 - 1.5 mm	11 mm	SR	305 mm 12,008 in	100 mm 3,937 in	165 mm 6,496 in	none
MF3/40-SRC	16 - 40 mm 0,630 - 1,575 in	0.4 - 1.5 mm	11 mm	SR C	305 mm 12,008 in	100 mm 3,937 in	165 mm 6,496 in	none
MF3/40-SSR	16 - 40 mm 0,630 - 1,575 in	Option	7 mm	None	305 mm 12,008 in	100 mm 3,937 in	165 mm 6,496 in	none
MF3/60	16 - 58 mm 0,630 - 2,283 in	0.4 - 1.5 mm	7 mm	SR	305 mm 12,008 in	115 mm 4,528 in	165 mm 6,496 in	none
MF3/60-C	16 - 58 mm 0,630 - 2,283 in	0.4 - 1.5 mm	7 mm	SR C	305 mm 12,008 in	115 mm 4,528 in	165 mm 6,496 in	none
MF3/60-SR	16 - 58 mm 0,630 - 2,283 in	0.4 - 1.5 mm	11 mm	SR	305 mm 12,008 in	115 mm 4,528 in	165 mm 6,496 in	none
MF3/60-SRC	16 - 58 mm 0,630 - 2,283 in	0.4 - 1.5 mm	11 mm	SR C	305 mm 12,008 in	115 mm 4,528 in	165 mm 6,496 in	none
MF3/60-SSR	16 - 58 mm 0,630 - 2,283 in	Option	7 mm	None	305 mm 12,008 in	115 mm 4,528 in	165 mm 6,496 in	none

