18.0 V CORDLESS HYDRAULIC CUTTING TOOL

general features











STORAGE							
Туре	Dimensions mm	Weight kg	Supplied with the tool	Purchase separately			
VALP40	520x432x126	2,6	*	_			

The tool is supplied as:

- Basic tool with battery and shoulder strap
- Spare battery
- Battery charger
- USB cable
- Plastic carrying case suitable for storing the tool and accessories



The blades are manufactured from high strength special Steel, heat The battery is equipped with LED indicators to show treated to ensure a the remaining battery life long service life. at any time by pressing the New Li-Ion 18 V 4 adjacent button.

OVERHEAD LINE APPLICATION

Next generation of 18.0 V

cordless hydraulic cutting tool specifically designed to cut Copper, Alumini-um, Aluminum-Steel ca-

bles (ACSR) having a max overall diameter of 50 mm.

Ah batteries offer a

higher capacity than

14.4 V 3 Ah, while great-

er cutting speed and cutting force

result from a revitalised hydraulic

OVERHEAD LINE APPLICATION

system with double speed action.

New

The head can rotate through 90 degrees, to enable the operator to work in the most comfortable position, and can easily be opened to allow cutting of running cables.

Fitted with a maximum hydraulic pressure valve.

Designed with improved balance, B-TC500YE is easily manageable during the cutting process and, by the use of bi-component plastics, has a shell with high resistance to wear and damage.

Rubber grip inserts, low noise and minimal vibration aid operator comfort while additional convenience and safety are provided by LED lighting of the working area. Operating temperature:

-15 to +50 ° C

Not suitable for cutting stay wire, Steel rope or earthing rod.

STORAGE

18.0 V CORDLESS HYDRAULIC CUTTING TOOL

general features




Max cutting Ø - mm	Dimensions mm			Dattam	Weight kg
	length	height	width	- Battery	(with battery)
55	441	424	87	18 N V 4 N Ah	8.9




Supplied with the tool



Purchase separately







VALP40

 Basic tool with battery and shoulder strap • Spare battery

Dimensions mm

520x432x126

- Battery charger
 USB cable
- Plastic carrying case suitable for storing the tool and accessories

The head can rotate through 320 degrees, to enable the operator to work in the most comfortable position, and can easily be opened to allow cutting of running cables.

Fitted with a maximum hydraulic pressure valve.

Designed with improved balance, B-TC550E is easily manageable during the cutting process and, by the use of bi-component plastics, has a shell with high resistance to wear and damage.

Rubber grip inserts, low noise and minimal vibration aid operator comfort while additional convenience and safety are provided by LED lighting of the working area.

For cutting capacity data see page 144.

Operating temperature: -15 to +50 ° C



hydraulic cutting tool Specifically designed cut Copper, Aldrey, Aluminium, Aluminium-Steel cables and Steel ropes, Aluminium and Steel rods having a max overall diameter of 55 mm. The blades are manufactured from high strength special Steel, heat treated to ensure a long service life.

New Li-lon 18 V 4 Ah batteries offer a higher capacity than 14.4 V 3 Ah, while greater cutting speed and

cutting force result from a revitalised hydraulic system with double speed action.

The battery is equipped with LED indicators to show the remaining battery life at any time by pressing the adjacent button.

