

### Certifications

Approved by ERDF

### Section

LV

### Application

Field



### PRODUCT BENEFITS

Ruler engraved in the tool to set the length of insulation to be removed

Compact and 6 different cable's section

Light and heavy duty

Other sections available on demand

### TOOL CAPACITY

<b>Diameter</b>	7,5 - 18 mm 0,295 - 0,709 inch
<b>Sections (mm<sup>2</sup>)</b>	16 - 25 - 35 - 54,6 - 70 - 150
<b>35mm<sup>2</sup> max length</b>	55 mm / 2,165 in
<b>54,6mm<sup>2</sup> max length</b>	70 mm / 2,756 in
<b>150mm<sup>2</sup> max length</b>	70 mm / 2,756 in

### TOOL DIMENSIONS

<b>Length</b>	130 mm
<b>Width</b>	130 mm
<b>Height</b>	40 mm
<b>Weight without box</b>	0,23 Kg
<b>Packaging</b>	None

### ALROC SAS

Z.I. de la Fonderie - 72160 TUFFE  
FRANCE

Phone: +33 2 43 71 11 80

Fax number : +33 2 43 71 16 51

www.alroc.fr

## Cable end strippers

### TO DO WHAT

The DBT enables the user to remove the insulation of secondary distribution cable ranging from 16 mm<sup>2</sup> up to 150 mm<sup>2</sup>



### Spare part

LDBT/7,5 - Spare blade for outer jacket of twisted cables

### Associated tool

MC45IR - Insulating composite cutting pliers

LV cables Tools

# DBT



Part Number	Diameter	Tool capacity				Dimensions			Packaging
		Sections (mm <sup>2</sup> )	35mm <sup>2</sup> max length	54,6mm <sup>2</sup> max length	150mm <sup>2</sup> max length	Length	Width	Height	
DBT	7,5 - 18 mm 0,295 - 0,709 in	16 - 25 - 35 - 54,6 - 70 - 150	55 mm / 2,165 in	70 mm / 2,756 in	70 mm / 2,756 in	130 mm 5,118 in	130 mm 5,118 in	40 mm 1,575 in	none



THORNE &  
**DERRICK**  
INTERNATIONAL

**Thorne & Derrick**  
+44 (0) 191 410 4292  
[www.powerandcables.com](http://www.powerandcables.com)