

## ST TYPE - SINGLE EYE DOUBLE WEAVE GRIP



This Slingco grip features a double weave construction for medium to heavy pulling applications in underground installations.

Slingco Part No	Range		Lattice Length		Approx. Break Load	
	in	mm	in	mm	lb	kg
<b>SHORT LENGTH - GALVANISED STEEL</b>						
ZCS2511	0.50 - 0.62	13-16	21	534	4,500	2,040
ZCS2512	0.62 - 0.75	16-19	24	610	5,600	2,540
ZCS2513	0.75 - 1.00	19-25	24	610	6,800	3,085
ZCS2514	1.00 - 1.50	25-38	24	610	9,600	4,355
ZCS2515	1.50 - 2.00	38-50	24	610	16,400	7,441
ZCS2516	2.00 - 2.50	50-63	24	610	18,500	8,390
ZCS2517	2.50 - 3.00	63-76	24	610	24,500	11,115
ZCS2518	3.00 - 3.50	76-89	24	610	24,500	11,115
ZCS2519	3.50 - 4.00	89-102	26	660	31,000	14,065
<b>LONGER LENGTH - GALVANISED STEEL</b>						
ZCS2520	0.75 - 1.00	19-25	36	914	6,800	3,085
ZCS2521	1.00 - 1.50	25-38	36	914	9,600	4,355
ZCS2522	1.50 - 2.00	38-50	36	914	16,400	7,440
ZCS2523	2.00 - 2.50	50-63	36	914	18,500	8,390
ZCS2524	2.50 - 3.00	63-76	36	914	24,500	11,115
ZCS2777	3.00 - 3.50	76-89	36	914	24,500	11,115
ZCS2778	3.50 - 4.00	89-102	40	1,010	31,000	14,065

## RT TYPE - ROTATING EYE DOUBLE WEAVE GRIP



Double weave construction for medium to heavy pulling applications in underground installations. Additionally its steel forged revolving head is ideal for connecting to Slingco swivels. Warning: The Slingco RT Type Rotating Eye Grip does not revolve under load. The rotating eye does not replace the need for a swivel. Please see page 17 for swivel and grip match-up and safety and technical information.

Slingco Part No	Range		Lattice Length		Approx. Break Load	
	in	mm	in	mm	lb	kg
<b>SHORT LENGTH - GALVANISED STEEL</b>						
ZCS2734	0.50 - 0.62	13-16	11	280	5,600	2,540
ZCS2735	0.62 - 0.75	16-19	11	280	6,800	3,085
ZCS2736	0.75 - 1.00	19-25	20	508	6,800	3,085
ZCS2738	1.00 - 1.50	25-38	21	533	12,800	5,805
ZCS2739	1.50 - 2.00	38-50	25	635	16,400	7,440
ZCS2740	2.00 - 2.50	50-63	26	660	27,200	12,340
ZCS2741	2.50 - 3.00	63-76	28	711	33,000	14,970
ZCS2742	3.00 - 3.50	76-89	30	762	41,000	18,600
ZCS2743	3.50 - 4.00	89-102	32	813	43,000	19,510
ZCS2744	4.00 - 4.50	102-115	33	838	43,000	19,510
<b>STANDARD - LONGER LENGTH - GALVANISED STEEL</b>						
ZCS2745	0.50 - 0.62	13-16	16	406	5,600	2,540
ZCS2746	0.62 - 0.75	16-19	16	406	6,800	4,355
ZCS2747	0.75 - 1.00	19-25	32	812	9,600	3,085
ZCS2748	1.25 - 1.50	25-38	33	838	16,400	5,805
ZCS2749	1.50 - 2.00	38-50	34	863	16,400	7,440
ZCS2750	2.00 - 2.50	50-63	36	914	27,300	12,340
ZCS2751	2.50 - 3.00	63-76	38	965	33,000	14,970
ZCS2752	3.00 - 3.50	76-89	39	990	41,000	18,600
ZCS2753	3.50 - 4.00	89-102	41	1,041	43,000	19,510
ZCS2754	4.00 - 4.50	102-115	42	1,066	43,000	19,510
ZCS2755	4.50 - 5.00	115-127	58	1,473	43,000	19,510
ZCS2756	5.00 - 6.00	127-153	60	1,524	43,000	19,510
ZCS2757	6.00 - 7.00	153-178	66	1,676	43,000	19,510