Cabinet base sealant - Black



2 component sealant used to seal the base of street cabinets.

For use in LV distribution cabinets, public lighting cabinets, cabinets for traffic control, and outdoor transformer station installations

Approved for use on the Highways & TFL sites

Features

- Available in 2 component mixing bags or 5L buckets
- Prevents ingress of moisture, pests and the instrusion of weeds, roots and plants
- Improves the climate inside the street cabinets and transformer stations
- Decrease interference of the equipment
- Extends the life of the components
- Quick and easy to apply
- Good flow properties
- Self levelling characteristics
- Good adhesion
- Smooth and non tacky surface



Cabinet base sealant - Black

Specifications

Properties	Unit	Value
Potlife (process time) 5°C	minutes	30
Potlife (process time) 23°C	minutes	10
Potlife (process time) 35°C	minutes	7
Gel-time	minutes	23
Viscosity (mixture) 25°C	Pa.s	ca. 3
Density	g/cm³	1.4
Hardness	Shore D	52
Tensile strength	N / mm²	4
Water absorption (30d/23°C)	%	<1.0
Weight loss 28d/120°C	%	0.8
Surface structure cured under water		no bubbles

Cabinet base sealant - Black

More info

- Installation instructions
- Dry and clean the interior walls of the cabinet Seal eventual holes and openings in the walls of the cabinet.
- Add dryed kiln sand to the bottom of the cabinet and make sure this is levelled,
- Mix the 2 component base sealant and pour this evenly over the bottom
- If necessary use several packages until the desired thickness is obtained

Products

Art.nr.	Product Name	Colour	Content	Order unit
205882 / 804660	Cabinet Base Sealant Black - 940ml	black	940ml	6 pcs/carton

