

FiloShrink Abandonment Kits



The Filoshrink AK-range is designed for use as a temporary or permanent cable abandonment on Low Voltage Cables up to and including 3.3kv.

Features



THORNE &
DERRICK
INTERNATIONAL

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com

FiloShrink Abandonment Kits

Specifications

Size of conductor	1 core Armoured	2 core Armoured	3 core Armoured	4 core Armoured	5 core Armoured
1.5mm ²	POA	AK 1	AK 1	AK 1	POA
2.5mm ²	POA	AK 1	AK 1	AK 1	POA
4mm ²	POA	AK 1	AK 1	AK 1	POA
6mm ²	POA	AK 1	AK 1	AK 2	POA
10mm ²	POA	AK 2	AK 2	AK 2	POA
16mm ²	POA	AK 2	AK 2	AK 2	POA
25mm ²	POA	AK 2	AK 2	AK 3	POA
35mm ²	POA	AK 2	AK 3	AK 3	POA
50mm ²	AK 2	AK 2	AK 3	AK 3	POA
70mm ²	AK 2	AK 3	AK 3	AK 3	POA
95mm ²	AK 2	AK 3	AK 3	AK 3	POA
120mm ²	AK 2	AK 3	AK 3	AK 4	POA
150mm ²	AK 3	AK 3	AK 4	AK 4	POA
185mm ²	AK 3	AK 4	AK 4	AK 5	POA
240mm ²	AK 3	AK 4	AK 4	AK 5	POA
300mm ²	AK 3	AK 4	AK 5	AK 5	POA
400mm ²	AK 4	AK 5	AK 5	AK 5	POA

All Filoshrink End Caps and Filoshrink EPDM Tubes have a 5-year shelf life, provided they are stored according to the manufacturers recommended conditions of storage.

FiloShrink Abandonment Kits

Products

Art.nr.	Product Name	Application cable diameter (mm)	Order unit
FiloShrink AK - 1	FiloShrink AK - 1	10,0 > 18,0	per piece
FiloShrink AK - 2	FiloShrink AK - 2	16,0 > 26,0	per piece
FiloShrink AK - 3	FiloShrink AK - 3	23,0 > 43,0	per piece
FiloShrink AK - 4	FiloShrink AK - 4	40,0 > 55,0	per piece
FiloShrink AK - 5	FiloShrink AK - 5	54,0 > 83,0	per piece