

ENSTO

Busbar connector

KG16

Code	KG16
GTIN	6418677400131
Name	Busbar connector Al 16-120 mm ² , Max thickness of the bar 10 mm
Description	The KG 16 connector is used for connecting Al-conductors to aluminium busbars or tin plated copper busbars in distribution boards, disconnectors, medium and low voltage transformer bushings.

Vendor



Technical specification

Others

ETIM Class: EC000001

Certificates

Standards: IEC 61238-1:2003

Features

Bolt: 2xM10

Dimensions

Conductor diameter: 4.6 ... 14 mm
 Conductor size Al: 16 ... 120 mm²
 Max. thickness of the bar: 10 mm
 Weight: 0.26 kg

Mechanical

Tightening torque Nm: 40 Nm

ETIM 7

Etim

Max. conductor cross section:	120 mm ²
Suitable for:	Flat rail
Suitable for round conductor connection:	True
Suitable for sector conductor connection:	True
Suitable for strip conductor connection:	True
Width clamp:	50 mm

Packaging

Pallet package

Unit:	pcs
Package size:	2625
Depth:	1200 mm
Width:	800 mm
Height:	890 mm

Default package

Unit:	pcs
Package size:	25
Depth:	218 mm
Width:	218 mm
Height:	126 mm
Volume:	5.988024 l



THORNE &
DERRICK
INTERNATIONAL

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com