

# ENSTO

Busbar connector

KG20

---

Code KG20  
 GTIN 6418677400186  
 Name Busbar connector  
 Cu 16-185 mm<sup>2</sup>  
 Description For connecting Cu-conductors to copper busbars in distribution boards, disconnectors, medium and low voltage transformer bushings.



Vendor

## Technical specification

---

### Others

ETIM Class: EC000001

### Certificates

Standards: IEC 61238-1:2003

### Features

Bolt: 2xM8

### Dimensions

Conductor diameter: 4.5 ... 17.5 mm

Conductor size Cu:  $\geq 16 \text{ mm}^2$

Max. thickness of the bar: 7.5 mm

Weight: 0.15 kg

### Mechanical

Tightening torque Nm: 22 Nm

## ETIM 7

---

### Etim

Max. conductor cross section: 185 mm<sup>2</sup>

Suitable for: Flat rail

Suitable for round conductor connection:	True
Suitable for sector conductor connection:	True
Suitable for strip conductor connection:	True
Width clamp:	48 mm

## Packaging

---

### Pallet package

Unit:	pcs
Package size:	5250
Depth:	1200 mm
Width:	800 mm
Height:	890 mm

### Default package

Unit:	pcs
Package size:	50
Depth:	218 mm
Width:	218 mm
Height:	126 mm
Volume:	5.988024 l



THORNE &  
**DERRICK**  
INTERNATIONAL

Thorne & Derrick  
+44 (0) 191 410 4292  
[www.powerandcables.com](http://www.powerandcables.com)