

# ENSTO

Busbar connector

KG26

---

Code KG26  
 GTIN 6418677400209  
 Name Busbar connector  
 Al 120-300 mm<sup>2</sup>  
 Description The KG26 connector is used for connecting Al-conductors to aluminium busbars or tin plated copper busbars in distribution boards, disconnectors, medium and low voltage transformer bushings.

Vendor



## Technical specification

---

### Others

ETIM Class: EC000001

### Certificates

Connector class: VDE 220 Teil 1/11.71 and Teil 2/11.71

Standards: SFS 2663

### Features

Bolt: 2xM12

### Dimensions

Conductor diameter: 14 ... 22.5 mm

Conductor size Al: 120 ... 300 mm<sup>2</sup>

Max. thickness of the bar: 15 mm

Weight: 0.74 kg

### Mechanical

Tightening torque Nm: 70 Nm

ETIM 7

---

## Etim

|                                           |                     |
|-------------------------------------------|---------------------|
| Max. conductor cross section:             | 300 mm <sup>2</sup> |
| Suitable for:                             | Flat rail           |
| Suitable for round conductor connection:  | True                |
| Suitable for sector conductor connection: | True                |
| Suitable for strip conductor connection:  | True                |
| Width clamp:                              | 70 mm               |

## Packaging

---

### Pallet package

|               |         |
|---------------|---------|
| Unit:         | pcs     |
| Package size: | 700     |
| Depth:        | 1200 mm |
| Width:        | 800 mm  |
| Height:       | 840 mm  |

### Default package

|               |            |
|---------------|------------|
| Unit:         | pcs        |
| Package size: | 10         |
| Depth:        | 218 mm     |
| Width:        | 218 mm     |
| Height:       | 176 mm     |
| Volume:       | 8.364224 l |



THORNE &  
**DERRICK**  
INTERNATIONAL

**Thorne & Derrick**  
+44 (0) 191 410 4292  
[www.powerandcables.com](http://www.powerandcables.com)