

ENSTO

Busbar connector

KG41

Code KG41
 GTIN 6418677400230
 Name Busbar connector
 Al 16-120 mm²

Description The KG41 connector is used for connecting Al-conductors to aluminium busbars or tin plated copper busbars in distribution boards, disconnectors, medium and low voltage transformer bushings. Max thickness of the bar 7.5 mm.

Vendor



Technical specification

Others

ETIM Class: EC000001

Features

Bolt: 2xM8

Dimensions

Conductor diameter: 4.6 ... 14 mm
 Conductor size Al: 16 ... 120 mm²
 Max. thickness of the bar: 7.5 mm
 Weight: 0.17 kg

Mechanical

Tightening torque Nm: 20 Nm

ETIM 7

Etim

Max. conductor cross section: 120 mm²
 Suitable for: Flat rail

Suitable for round conductor connection:	True
Suitable for sector conductor connection:	True
Suitable for strip conductor connection:	True
Width clamp:	44 mm

Packaging

Pallet package

Unit:	pcs
Package size:	3500
Depth:	1200 mm
Width:	800 mm
Height:	840 mm

Default package

Unit:	pcs
Package size:	50
Depth:	220 mm
Width:	220 mm
Height:	175 mm
Volume:	8.47 l



Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com