

ENSTO

Busbar connector

KG71

Code KG71
 GTIN 6418677400322
 Name Busbar connector
 Al 16-120 mm² / Cu 10-95 mm²
 Description The KG71 is used for connecting insulated Al- and Cu-conductors without stripping to aluminium busbars in distribution boards, disconnectors, medium and low voltage transformer bushings. Max thickness of the bar 7.5 mm.

Vendor



Technical specification

Others

ETIM Class: EC000001

Certificates

Standards: SFS 2663

Features

Bolt: 2xM8

Dimensions

Conductor diameter: 6 ... 18 mm
 Conductor size Al: 16 ... 120 mm²
 Conductor size Cu: 10 ... 20 mm²
 Max. thickness of the bar: 7.5 mm
 Weight: 0.2 kg

Mechanical

Tightening torque Nm: 20 Nm

ETIM 7

Etim

Max. conductor cross section:	120 mm ²
Suitable for:	Flat rail
Suitable for round conductor connection:	True
Suitable for sector conductor connection:	True
Suitable for strip conductor connection:	True
Width clamp:	50 mm

Packaging

Pallet package

Unit:	pcs
Package size:	3150
Depth:	1200 mm
Width:	800 mm
Height:	1050 mm

Default package

Unit:	pcs
Package size:	50
Depth:	385 mm
Width:	260 mm
Height:	130 mm
Volume:	13.013 l



THORNE &
DERRICK
INTERNATIONAL

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com