

ENSTO

Insulation piercing connector

SL11.118

Code SL11.118
 GTIN 6418677403538
 Name Insulation piercing connector
 Al 10-95 mm² or Cu 1.5-70 mm²
 Description Universal connector for all combinations of aluminium and copper main and branch connectors. SL11.118 is for PEX insulated conductor.

Vendor



Technical specification

Others

ETIM Class: EC001062

Features

Bolt: M8

Dimensions

Branch conductor mm²: Al 10-95 / Cu 1.5-70

Conductor diameter: 3 ... 16 mm

Main conductor mm²: Al 10-95 / Cu 1.5-70

Weight: 0.12 kg

Mechanical

Tightening torque Nm: 26 Nm

ETIM 7

Etim

Clamping channel opening branch conductor: Closed

Clamping channel opening main conductor: Closed

Material branch conductor: Aluminium/copper

Material main conductor: Aluminium/copper

Nominal cross section branch conductor SE/RE:	1.5 ... 95 mm ²
Nominal cross section branch conductor SM/RM:	1.5 ... 95 mm ²
Nominal cross section main conductor SE:	1.5 ... 95 mm ²
Nominal cross section main conductor SM:	1.5 ... 95 mm ²
Surface protection:	Tinned
Terminal insulated:	True
Type of connection:	Insulation piercing connector IPC

Packaging

Pallet package

Unit:	PCE
Package size:	3150
Depth:	1200 mm
Width:	800 mm
Height:	1050 mm

Default package

Unit:	PCE
Package size:	50
Depth:	385 mm
Width:	260 mm
Height:	130 mm
Volume:	13.013 l



**THORNE &
DERRICK**
INTERNATIONAL

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com