

ENSTO

IPC / Bare connector

SL9.11

Code	SL9.11
GTIN	6418677403804
Name	IPC / Bare connector AL 16-120 mm ² and Al 16-35 mm ²
Description	SL9.11 is used for aluminium to aluminium connections. The connector has one bolt.
Vendor	



Technical specification

Others

ETIM Class:	EC001062
-------------	----------

Certificates

Standards:	SFS 2663
------------	----------

Dimensions

Branch conductor mm ² :	Al 16-35
Main conductor mm ² :	Al 16-120
Weight:	0.1 kg

Mechanical

Tightening torque Nm:	20 Nm
-----------------------	-------

ETIM 7

Etim

Clamping channel opening branch conductor:	Closed
--	--------

Clamping channel opening main conductor: Closed

Material branch conductor:	Aluminium
----------------------------	-----------

Material main conductor:	Aluminium
--------------------------	-----------

Nominal cross section branch conductor SE/RE:	16 ... 35 mm ²
---	---------------------------

Nominal cross section branch conductor SM/RM:	16 ... 35 mm ²
Nominal cross section main conductor SE:	16 ... 120 mm ²
Nominal cross section main conductor SM:	16 ... 120 mm ²
Surface protection:	Bare
Terminal insulated:	True
Type of connection:	Insulation piercing connector IPC

Packaging

Pallet package

Unit:	PCE
Package size:	1800
Depth:	1200 mm
Width:	800 mm
Height:	1020 mm

Default package

Unit:	PCE
Package size:	50
Depth:	400 mm
Width:	265 mm
Height:	220 mm
Volume:	23.32 l



THORNE &
DERRICK
INTERNATIONAL

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com