

ENSTO

IPC / Bare connector

SL9.22

Code	SL9.22
GTIN	6418677403835
Name	IPC / Bare connector Al 16-120 mm ² and Al 16-95 mm ²
Description	The SL 9.22 connector is equipped with a threaded hole for a surge arrester.
Vendor	



Technical specification

Others

ETIM Class:	EC001062
-------------	----------

Certificates

Standards:	EN 50483-4:2009
------------	-----------------

Features

Allen screws:	M8
---------------	----

Dimensions

Branch conductor mm ² :	Al 16-95
Conductor diameter mm:	7-18 / 4.6-12
Main conductor mm ² :	Al 16-120
Weight:	0.15 kg

Mechanical

Tightening torque Nm:	20 Nm
-----------------------	-------

ETIM 7

Etim

Clamping channel opening branch conductor:	Closed
Clamping channel opening main conductor:	Closed
Material branch conductor:	Aluminium

Material main conductor:	Aluminium
Nominal cross section branch conductor SE/RE:	16 ... 95 mm ²
Nominal cross section branch conductor SM/RM:	16 ... 95 mm ²
Nominal cross section main conductor SE:	16 ... 120 mm ²
Nominal cross section main conductor SM:	16 ... 120 mm ²
Surface protection:	Bare
Terminal insulated:	True
Type of connection:	Insulation piercing connector IPC

Packaging

Pallet package

Unit:	PCE
Package size:	1800
Depth:	1200 mm
Width:	800 mm
Height:	1200 mm

Default package

Unit:	PCE
Package size:	50
Depth:	400 mm
Width:	265 mm
Height:	220 mm
Volume:	23.32 l



**THORNE &
DERRICK**
INTERNATIONAL

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com