

# ENSTO

Insulation piercing connector

SLIP12.05

---

Code	SLIP12.05
GTIN	6418677441783
Name	Insulation piercing connector Al/Cu 10-50mm <sup>2</sup> and Al/Cu 1.5-50mm <sup>2</sup>
Description	The SLIP12.05 is used for all connections of insulated aluminium and copper main and branch conductors up to 1000Vac. The design enables hot line installation. Equipped with shear head screw.

Vendor

## Technical specification

---

### Others

ETIM Class:	EC001062
-------------	----------

### Certificates

Connector class:	A2
Standards:	EN 50483-4:2009

### Features

Bolt:	M8x50
-------	-------

### Dimensions

Conductor diameter:	3 ... 12.1 mm
Main conductor mm <sup>2</sup> :	10-50
Net Weight:	0.1 kg
Weight:	0.1 kg

### Mechanical

Tightening torque Nm:	23.5 Nm
-----------------------	---------

ETIM 7

---

Etim



Clamping channel opening branch conductor:	Closed
Clamping channel opening main conductor:	Closed
Material branch conductor:	Aluminium/copper
Material main conductor:	Aluminium/copper
Nominal cross section branch conductor SE/RE:	1.5 ... 50 mm <sup>2</sup>
Nominal cross section branch conductor SM/RM:	1.5 ... 50 mm <sup>2</sup>
Nominal cross section main conductor SE:	10 ... 50 mm <sup>2</sup>
Nominal cross section main conductor SM:	10 ... 50 mm <sup>2</sup>
Surface protection:	Tinned
Terminal insulated:	True
Type of connection:	Insulation piercing connector IPC

## Packaging

---

### Pallet package

Unit:	PCE
Package size:	2700
Depth:	1200 mm
Width:	800 mm

### Default package

Unit:	PCE
Package size:	50
Depth:	383 mm
Width:	258 mm
Height:	173 mm
Weight:	5.242 kg
Volume:	17.094822 l