

ENSTO

IPC / Bare connector

SLIP12.127

Code SLIP12.127
 GTIN 6418677446023
 Name IPC / Bare connector
 Al/Cu 10-70 mm² to Al/Cu 1.5-50 mm²
 Description SLIP12.127 is for all connections of uninsulated aluminium or copper main and insulated branch conductors up to 1000 VAC. Equipped with shear head screw.

Vendor

Technical specification

Others

ETIM Class: EC001062

Certificates

Connector class: A2

Standards: EN 50483-4:2009

Features

Bolt: M8x50

Mechanical

Tightening torque Nm: 23.5 Nm

Electrical values

Highest system voltage: 1 kV

ETIM 7

Etim

Clamping channel opening branch conductor: Closed

Clamping channel opening main conductor: Closed



Material branch conductor:	Aluminium/copper
Material main conductor:	Aluminium/copper
Nominal cross section branch conductor SE/RE:	1.5 ... 50 mm ²
Nominal cross section branch conductor SM/RM:	1.5 ... 50 mm ²
Nominal cross section main conductor SE:	10 ... 70 mm ²
Nominal cross section main conductor SM:	10 ... 70 mm ²
Surface protection:	Tinned
Terminal insulated:	True
Type of connection:	Insulation piercing connector IPC

Packaging

Pallet package

Unit:	PCE
Package size:	2700
Depth:	1200 mm
Width:	800 mm
Height:	1140 mm

Default package

Unit:	PCE
Package size:	50
Depth:	385 mm
Width:	260 mm
Height:	165 mm
Volume:	16.5165 l



Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com