

ENSTO

IPC / Bare connector

SLIP22.127

Code SLIP22.127
 GTIN 6418677416194
 Name IPC / Bare connector
 Main Al 25-95 or Cu 25-70 Branch Al 2.5-95 or Cu 1.5-70 mm²
 Description SLIP22.127 is for all connections of uninsulated aluminium and copper main and insulated branch conductors up to 1000 VAC. Equipped with shear head screw.

Vendor



Technical specification

Others

ETIM Class: EC001062

Certificates

Connector class: A2

Standards: EN 50483-4:2009

Features

Bolt: M8x50

Drawing markings

d1: 6.5-16.0

d2: 3.0-16.0

Mechanical

Tightening torque Nm: 18.5 Nm

Electrical values

Highest system voltage: 1 kV

ETIM 7

Etim

Clamping channel opening branch conductor:	Closed
Clamping channel opening main conductor:	Closed
Material branch conductor:	Aluminium/copper
Material main conductor:	Aluminium/copper
Nominal cross section branch conductor SE/RE:	2.5 ... 95 mm ²
Nominal cross section branch conductor SM/RM:	2.5 ... 95 mm ²
Nominal cross section main conductor SE:	25 ... 95 mm ²
Nominal cross section main conductor SM:	25 ... 95 mm ²
Surface protection:	Tinned
Terminal insulated:	True
Type of connection:	Insulation piercing connector IPC

Packaging

Pallet package

Unit:	PCE
Package size:	2700
Depth:	1200 mm
Width:	800 mm
Height:	1140 mm

Default package

Unit:	PCE
Package size:	50
Depth:	385 mm
Width:	260 mm
Height:	165 mm
Volume:	16.5165 l



THORNE &
DERRICK
INTERNATIONAL

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com