

ENSTO

Insulation piercing connector

SLIP32.2

Code SLIP32.2
 GTIN 6418677442001
 Name Insulation piercing connector
 Main Al 16-150 or Cu 16-150 Branch Al 16-120 or Cu 16-95 mm²
 Description The SLIP32.2 is for all connections of insulated aluminium and copper main and branch conductors up to 1000 VAC. The design enables hot line installation. The shear head is insulated from the bolt and the connector body. Equipped with shear head screw.

Vendor



Technical specification

Others

ETIM Class: EC001062

Certificates

Standards: EN 50483-4:2009

Features

Bolt: M8x75

Mechanical

Tightening torque Nm: 18.25 Nm

Electrical values

Highest system voltage: 1 kV

ETIM 7

Etim

Clamping channel opening branch conductor:	Closed
Clamping channel opening main conductor:	Closed
Material branch conductor:	Aluminium/copper
Material main conductor:	Aluminium/copper
Nominal cross section branch conductor SE/RE:	16 ... 120 mm ²
Nominal cross section branch conductor SM/RM:	16 ... 120 mm ²
Nominal cross section main conductor SE:	16 ... 150 mm ²
Nominal cross section main conductor SM:	16 ... 150 mm ²
Surface protection:	Tinned
Terminal insulated:	True
Type of connection:	Insulation piercing connector IPC

Packaging

Pallet package

Unit:	PCE
Package size:	3150
Depth:	1200 mm
Width:	800 mm
Height:	1050 mm

Default package

Unit:	PCE
Package size:	50
Depth:	385 mm
Width:	260 mm
Height:	130 mm
Volume:	13.013 l



THORNE &
DERRICK
INTERNATIONAL

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com