

ENSTO

Insulation piercing connector

SLIW56



Code	SLIW56
GTIN	6438100303792
Name	Insulation piercing connector 25-150 mm ² / 6-35 mm ² , Waterproof
Description	SLIW56 is for use with insulated aluminium or copper conductors. Fully insulated bolt provides safe live line working. Both main and branch conductor insulations are pierced by single bolt action. Test voltage 6 kV/50 Hz/1 min in water. Connector's design enables live line installation without peeling insulation from conductor.

Vendor

Technical specification

Others

ETIM Class: EC001062

Certificates

Standards: EN 50483-4:2009

Dimensions

Branch conductor mm²: 6-35
 Conductor diameter mm: 8.0-18.6 / 4.0-10.9
 Main conductor mm²: 25-150
 Weight: 0.07 kg

Mechanical

Tightening torque Nm: 13 Nm

Electrical values

Highest system voltage: 1 kV
 Test voltage in water: 6 kV / 50 Hz / 1 min



THORNE &
DERRICK
INTERNATIONAL

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com

ETIM 7

Etim

Clamping channel opening branch conductor:	Both sides open
Clamping channel opening main conductor:	Both sides open
Material branch conductor:	Aluminium/copper
Material main conductor:	Aluminium/copper
Nominal cross section branch conductor SE/RE:	6 ... 35 mm ²
Nominal cross section branch conductor SM/RM:	6 ... 35 mm ²
Nominal cross section main conductor SE:	25 ... 150 mm ²
Nominal cross section main conductor SM:	25 ... 150 mm ²
Surface protection:	Tinned
Terminal insulated:	True
Type of connection:	Insulation piercing connector IPC

Packaging

Pallet package

Unit:	pcs
Package size:	3240
Depth:	1200 mm
Width:	800 mm
Height:	1140 mm

Default package

Unit:	pcs
Package size:	60
Depth:	380 mm
Width:	250 mm
Height:	165 mm
Volume:	15.675 l



**THORNE &
DERRICK**
INTERNATIONAL

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com